

別添資料1 空気呼吸・空気減圧表

減圧速度 80kPa／min
安全率の設定:1.00

帯底圧力 (kPa)			帯底圧力 (msw)			高圧下 時間(min)	He(%)	N2(%)	空気呼吸 減圧速度80kPa/min				空気呼吸 減圧速度80kPa/min				減圧時間	総業務 時間	別表1 差	別表2 差
を 超え		以下	を 超え		以下				240	210	180	150	120	90	60	30				
80	～	100	8	～	10	10	0	79									1	11		
80	～	100	8	～	10	20	0	79									1	21		
80	～	100	8	～	10	30	0	79									1	31		
80	～	100	8	～	10	40	0	79									1	41		
80	～	100	8	～	10	50	0	79									1	51		
80	～	100	8	～	10	60	0	79									1	61		
80	～	100	8	～	10	70	0	79									1	71		
80	～	100	8	～	10	80	0	79									1	81		
80	～	100	8	～	10	90	0	79									1	91		
80	～	100	8	～	10	100	0	79									1	101		
80	～	100	8	～	10	110	0	79									1	111		
80	～	100	8	～	10	120	0	79									1	121		
80	～	100	8	～	10	130	0	79									1	131		
80	～	100	8	～	10	140	0	79									1	141		
80	～	100	8	～	10	150	0	79									1	151		
80	～	100	8	～	10	160	0	79									1	161		
80	～	100	8	～	10	170	0	79									1	171		
80	～	100	8	～	10	180	0	79									1	181		
80	～	100	8	～	10	190	0	79									1	191		
80	～	100	8	～	10	200	0	79									1	201		
80	～	100	8	～	10	210	0	79									1	211		
80	～	100	8	～	10	220	0	79									1	221		
80	～	100	8	～	10	230	0	79									1	231		
80	～	100	8	～	10	240	0	79									1	241		
80	～	100	8	～	10	250	0	79									1	251		
80	～	100	8	～	10	260	0	79									1	261		
80	～	100	8	～	10	270	0	79									1	271		
80	～	100	8	～	10	280	0	79									1	281		
80	～	100	8	～	10	290	0	79									1	291		
80	～	100	8	～	10	300	0	79									1	301		
80	～	100	8	～	10	310	0	79									1	311		
80	～	100	8	～	10	320	0	79									1	321		
80	～	100	8	～	10	330	0	79									1	331		
80	～	100	8	～	10	340	0	79									1	341		
80	～	100	8	～	10	350	0	79									1	351		
80	～	100	8	～	10	360	0	79									1	361		
80	～	100	8	～	10	370	0	79									1	371		
80	～	100	8	～	10	380	0	79									1	381		
80	～	100	8	～	10	390	0	79									1	391		
80	～	100	8	～	10	400	0	79									1	401		
80	～	100	8	～	10	410	0	79									1	411		
80	～	100	8	～	10	420	0	79									1	421		
80	～	100	8	～	10	430	0	79									1	431		
80	～	100	8	～	10	440	0	79									1	441		
80	～	100	8	～	10	450	0	79									1	451		
80	～	100	8	～	10	460	0	79									1	461		
80	～	100	8	～	10	470	0	79									1	471		
80	～	100	8	～	10	480	0	79									1	481		
80	～	100	8	～	10	490	0	79									1	491		
80	～	100	8	～	10	500	0	79									1	501		
80	～	100	8	～	10	510	0	79									1	511		
80	～	100	8	～	10	520	0	79									1	521		
80	～	100	8	～	10	530	0	79									1	531		
80	～	100	8	～	10	540	0	79									1	541		
80	～	100	8	～	10	550	0	79									1	551		
80	～	100	8	～	10	560	0	79									1	561		
80	～	100	8	～	10	570	0	79								1	2	572		
80	～	100	8	～	10	580	0	79								2	3	583		
80	～	100	8	～	10	590	0	79								3	4	594		
100	～	120	10	～	12	10	0	79									2	12		0
100	～	120	10	～	12	20	0	79									2	22		
100	～	120	10	～	12	30	0	79									2	32	-1	0
100	～	120	10	～	12	40	0	79									2	42		
100	～	120	10	～	12	50	0	79									2	52		
100	～	120	10	～	12	60	0	79									2	62	-1	0
100	～	120	10	～	12	70	0	79									2	72		
100	～	120	10	～	12	80	0	79									2	82		
100	～	120	10	～	12	90	0	79									2	92	-1	0
100	～	120	10	～	12	100	0	79									2	102		
100	～	120	10	～	12	110	0	79									2	112		
100	～	120	10	～	12	120	0	79									2	122	-1	0
100	～	120	10	～	12	130	0	79									2	132		
100	～	120	10	～	12	140	0	79									2	142		
100	～	120	10	～	12	150	0	79									2	152	-2	
100	～	120	10	～	12	160	0	79									2	162		
100	～	120	10	～	12	170	0	79									2	172		
100	～	120	10	～	12	180	0	79									2	182	-3	-3
100	～	120	10	～	12	190	0	79									2	192		
100	～	120	10	～	12	200	0	79									2	202		
100	～	120	10	～	12	210	0	79									2	212	-4	
100	～	120	10	～	12	220	0	79									2	222		
100	～	120	10	～	12	230	0	79									2	232		
100	～	120	10	～	12	240	0	79									2	242	-5	-5
100	～	120	10	～	12	250	0	79									2	252		
100	～	120	10	～	12	260	0	79								1	3	263		
100	～	120	10	～	12	270	0	79								3	5	275	-2	
100	～	120	10	～	12	280	0	79								4	6	286		
100	～	120	10	～	12	290	0	79								5	7	297		
100	～	120	10	～	12	300	0	79								6	8	308	0	
100	～	120	10	～	12	310	0	79								7	9	319		
100	～	120	10	～	12	320	0	79								8	10	330		
100	～	120	10	～	12	330	0	79								9	11	341	3	
100	～	120	10	～	12	340	0	79								11	13	353		

安全率の設定:1.00

帯底圧力 (kPa)			帯底圧力 (msw)			高圧下 時間(min)	He(%)	N2(%)	空気呼吸 減圧速度80kPa/min				空気呼吸 減圧速度80kPa/min				減圧時間	総業務 時間	別表1 差	別表2 差
を 超え		以下	を 超え		以下				240	210	180	150	120	90	60	30				
100	～	120	10	～	12	350	0	79								13	15	365		
100	～	120	10	～	12	360	0	79								15	17	377	8	8
100	～	120	10	～	12	370	0	79								18	20	390		
100	～	120	10	～	12	380	0	79								21	23	403		
100	～	120	10	～	12	390	0	79								24	26	416		
100	～	120	10	～	12	400	0	79								27	29	429		
100	～	120	10	～	12	410	0	79								29	31	441		
100	～	120	10	～	12	420	0	79								32	34	454		
100	～	120	10	～	12	430	0	79								34	36	466		
100	～	120	10	～	12	440	0	79								36	38	478		
100	～	120	10	～	12	450	0	79								38	40	490		
100	～	120	10	～	12	460	0	79								42	44	504		
100	～	120	10	～	12	470	0	79								45	47	517		
100	～	120	10	～	12	480	0	79								48	50	530		
100	～	120	10	～	12	490	0	79								51	53	543		
100	～	120	10	～	12	500	0	79								54	56	556		
100	～	120	10	～	12	510	0	79								57	59	569		
100	～	120	10	～	12	520	0	79								59	61	581		
100	～	120	10	～	12	530	0	79								62	64	594		
120	～	140	12	～	14	10	0	79									2	12		0
120	～	140	12	～	14	20	0	79									2	22		
120	～	140	12	～	14	30	0	79									2	32	-1	0
120	～	140	12	～	14	40	0	79									2	42		
120	～	140	12	～	14	50	0	79									2	52		
120	～	140	12	～	14	60	0	79									2	62	-1	0
120	～	140	12	～	14	70	0	79									2	72		
120	～	140	12	～	14	80	0	79									2	82		
120	～	140	12	～	14	90	0	79									2	92	-1	0
120	～	140	12	～	14	100	0	79									2	102		
120	～	140	12	～	14	110	0	79									2	112		
120	～	140	12	～	14	120	0	79									2	122	-3	-4
120	～	140	12	～	14	130	0	79									2	132		
120	～	140	12	～	14	140	0	79									2	142		
120	～	140	12	～	14	150	0	79								1	3	153	-4	-5
120	～	140	12	～	14	160	0	79								3	5	165		
120	～	140	12	～	14	170	0	79								5	7	177		
120	～	140	12	～	14	180	0	79								6	8	188	0	-1
120	～	140	12	～	14	190	0	79								9	11	201		
120	～	140	12	～	14	200	0	79								12	14	214		
120	～	140	12	～	14	210	0	79								14	16	226	6	5
120	～	140	12	～	14	220	0	79								17	19	239		
120	～	140	12	～	14	230	0	79								19	21	251		
120	～	140	12	～	14	240	0	79								21	23	263	11	11
120	～	140	12	～	14	250	0	79								23	25	275		
120	～	140	12	～	14	260	0	79								24	26	286		
120	～	140	12	～	14	270	0	79								27	29	299	17	
120	～	140	12	～	14	280	0	79								30	32	312		
120	～	140	12	～	14	290	0	79								33	35	325		
120	～	140	12	～	14	300	0	79								37	39	339	27	25
120	～	140	12	～	14	310	0	79								42	44	354		
120	～	140	12	～	14	320	0	79								46	48	368		
120	～	140	12	～	14	330	0	79								50	52	382	38	
120	～	140	12	～	14	340	0	79								54	56	396		
120	～	140	12	～	14	350	0	79								57	59	409		
120	～	140	12	～	14	360	0	79								60	62	422		
120	～	140	12	～	14	370	0	79								64	66	436		
120	～	140	12	～	14	380	0	79								69	71	451		
120	～	140	12	～	14	390	0	79								74	76	466		
120	～	140	12	～	14	400	0	79								78	80	480		
120	～	140	12	～	14	410	0	79								82	84	494		
120	～	140	12	～	14	420	0	79								86	88	508		
120	～	140	12	～	14	430	0	79								90	92	522		
120	～	140	12	～	14	440	0	79								94	96	536		
120	～	140	12	～	14	450	0	79								97	99	549		
120	～	140	12	～	14	460	0	79								100	102	562		
120	～	140	12	～	14	470	0	79								105	107	577		
120	～	140	12	～	14	480	0	79								113	115	595		
140	～	160	14	～	16	10	0	79									2	12		0
140	～	160	14	～	16	20	0	79									2	22		
140	～	160	14	～	16	30	0	79									2	32	-1	0
140	～	160	14	～	16	40	0	79									2	42		
140	～	160	14	～	16	50	0	79									2	52		0
140	～	160	14	～	16	60	0	79									2	62	-1	
140	～	160	14	～	16	70	0	79									2	72		0
140	～	160	14	～	16	80	0	79									2	82		
140	～	160	14	～	16	90	0	79									2	92	-3	-3
140	～	160	14	～	16	100	0	79								1	3	103		
140	～	160	14	～	16	110	0	79								3	5	115		
140	～	160	14	～	16	120	0	79								5	7	127	0	-1
140	～	160	14	～	16	130	0	79								9	11	141		
140	～	160	14	～	16	140	0	79								12	14	154		
140	～	160	14	～	16	150	0	79								14	16	166	7	5
140	～	160	14	～	16	160	0	79								18	20	180		
140	～	160	14	～	16	170	0	79								22	24	194		
140	～	160	14	～	16	180	0	79								25	27	207	16	13
140	～	160	14	～	16	190	0	79								29	31	221		
140	～	160	14	～	16	200	0	79								31	33	233		
140	～	160	14	～	16	210	0	79								34	36	246	23	21
140	～	160	14	～	16	220	0	79								36	38	258		
140	～	160	14	～	16	230	0	79								41	43	273		
140	～	160	14	～	16	240	0	79								45	47	287	30	
140	～	160	14	～	16	250	0	79								49	51	301		
140	～	160	14	～	16	260	0	79								55	57	317		
140	～	160	14	～	16	270	0	79								61	63	333	43	44
140	～	160	14	～	16	280	0	79								66	68	348		

安全率の設定:1.00

帯底圧力 (kPa)			帯底圧力 (msw)			高圧下 時間(min)	He(%)	N2(%)	空気呼吸 減圧速度80kPa/min				空気呼吸 減圧速度80kPa/min				減圧時間	総業務 時間	別表1 差	別表2 差
を超え		以下	を超え	～	以下				240	210	180	150	120	90	60	30				
140	～	160	14	～	16	300	0	79								76	78	378	53	
140	～	160	14	～	16	310	0	79								80	82	392		
140	～	160	14	～	16	320	0	79							1	86	89	409		
140	～	160	14	～	16	330	0	79							2	91	95	425		
140	～	160	14	～	16	340	0	79							3	97	102	442		
140	～	160	14	～	16	350	0	79							4	101	107	457		
140	～	160	14	～	16	360	0	79							4	107	113	473		
140	～	160	14	～	16	370	0	79							5	111	118	488		
140	～	160	14	～	16	380	0	79							6	115	123	503		
140	～	160	14	～	16	390	0	79							7	118	127	517		
140	～	160	14	～	16	400	0	79							9	123	134	534		
140	～	160	14	～	16	410	0	79							10	133	145	555		
140	～	160	14	～	16	420	0	79							11	142	155	575		
140	～	160	14	～	16	430	0	79							13	150	165	595		
160	～	180	16	～	18	10	0	79									2	12		0
160	～	180	16	～	18	20	0	79									2	22		
160	～	180	16	～	18	30	0	79									2	32	-1	
160	～	180	16	～	18	40	0	79									2	42		0
160	～	180	16	～	18	50	0	79									2	52		
160	～	180	16	～	18	60	0	79									2	62	-5	
160	～	180	16	～	18	70	0	79									2	72		
160	～	180	16	～	18	80	0	79								2	4	84		
160	～	180	16	～	18	90	0	79								6	8	98	-3	
160	～	180	16	～	18	100	0	79								9	11	111		
160	～	180	16	～	18	110	0	79								13	15	125		
160	～	180	16	～	18	120	0	79								17	19	139	4	
160	～	180	16	～	18	130	0	79								21	23	153		
160	～	180	16	～	18	140	0	79								25	27	167		
160	～	180	16	～	18	150	0	79								30	32	182	13	10
160	～	180	16	～	18	160	0	79								35	37	197		
160	～	180	16	～	18	170	0	79								39	41	211		
160	～	180	16	～	18	180	0	79								42	44	224	17	19
160	～	180	16	～	18	190	0	79							1	45	48	238		
160	～	180	16	～	18	200	0	79							3	49	54	254		
160	～	180	16	～	18	210	0	79							4	53	59	269	24	
160	～	180	16	～	18	220	0	79							5	59	66	286		
160	～	180	16	～	18	230	0	79							8	65	75	305		
160	～	180	16	～	18	240	0	79							10	70	82	322	41	50
160	～	180	16	～	18	250	0	79							12	75	89	339		
160	～	180	16	～	18	260	0	79							14	80	96	356		
160	～	180	16	～	18	270	0	79							16	84	102	372	55	
160	～	180	16	～	18	280	0	79							17	91	110	390		
160	～	180	16	～	18	290	0	79							19	98	119	409		
160	～	180	16	～	18	300	0	79							20	104	126	426	72	
160	～	180	16	～	18	310	0	79							21	110	133	443		
160	～	180	16	～	18	320	0	79							23	114	139	459		
160	～	180	16	～	18	330	0	79							26	118	146	476		
160	～	180	16	～	18	340	0	79							28	123	153	493		
160	～	180	16	～	18	350	0	79							30	132	164	514		
160	～	180	16	～	18	360	0	79							32	142	176	536		
160	～	180	16	～	18	370	0	79							36	152	190	560		
160	～	180	16	～	18	380	0	79							40	160	202	582		
180	～	200	18	～	20	10	0	79									3	13		0
180	～	200	18	～	20	20	0	79									3	23		
180	～	200	18	～	20	30	0	79									3	33	-1	
180	～	200	18	～	20	40	0	79									3	43		
180	～	200	18	～	20	50	0	79									3	53		0
180	～	200	18	～	20	60	0	79								1	4	64	-7	
180	～	200	18	～	20	70	0	79								5	8	78		
180	～	200	18	～	20	80	0	79								10	13	93		
180	～	200	18	～	20	90	0	79								13	16	106	-3	
180	～	200	18	～	20	100	0	79								19	22	122		
180	～	200	18	～	20	110	0	79								24	27	137		
180	～	200	18	～	20	120	0	79								28	31	151	6	
180	～	200	18	～	20	130	0	79							2	33	38	168		
180	～	200	18	～	20	140	0	79							3	38	44	184		
180	～	200	18	～	20	150	0	79							6	41	50	200	18	
180	～	200	18	～	20	160	0	79							8	44	55	215		
180	～	200	18	～	20	170	0	79							10	48	61	231		
180	～	200	18	～	20	180	0	79							12	53	68	248	24	
180	～	200	18	～	20	190	0	79							15	57	75	265		
180	～	200	18	～	20	200	0	79							18	64	85	285		
180	～	200	18	～	20	210	0	79							21	71	95	305	42	
180	～	200	18	～	20	220	0	79							24	76	103	323		
180	～	200	18	～	20	230	0	79							26	82	111	341		
180	～	200	18	～	20	240	0	79							28	88	119	359	56	
180	～	200	18	～	20	250	0	79							30	96	129	379		
180	～	200	18	～	20	260	0	79							32	103	138	398		
180	～	200	18	～	20	270	0	79							35	109	147	417	74	
180	～	200	18	～	20	280	0	79							38	115	156	436		
180	～	200	18	～	20	290	0	79							41	120	164	454		
180	～	200	18	～	20	300	0	79							44	126	173	473		
180	～	200	18	～	20	310	0	79							47	136	186	496		
180	～	200	18	～	20	320	0	79							52	147	202	522		
180	～	200	18	～	20	330	0	79							57	157	217	547		
180	～	200	18	～	20	340	0	79							61	167	231	571		
180	～	200	18	～	20	350	0	79							65	177	245	595		
200	～	220	20	～	22	10	0	79									3	13		
200	～	220	20	～	22	20	0	79									3	23		
200	～	220	20	～	22	30	0	79									3	33	-1	0
200	～	220	20	～	22	40	0	79									3	43		
200	～	220	20	～	22	50	0	79								2	5	55		
200	～	220	20	～	22	60	0	79								6	9	69	-5	-1
200	～	220	20	～	22	70														

安全率の設定:1.00

帯底圧力 (kPa)			帯底圧力 (msw)			高圧下 時間(min)	He(%)	N2(%)	空気呼吸 減圧速度80kPa/min				空気呼吸 減圧速度80kPa/min				減圧時間	総業務 時間	別表1 差	別表2 差
を 超え		以下	を 超え		以下				240	210	180	150	120	90	60	30				
200	～	220	20	～	22	100	0	79							3	26	32	132		1
200	～	220	20	～	22	110	0	79							5	31	39	149		
200	～	220	20	～	22	120	0	79							8	36	47	167	12	5
200	～	220	20	～	22	130	0	79							11	40	54	184		
200	～	220	20	～	22	140	0	79							14	43	60	200		
200	～	220	20	～	22	150	0	79							17	47	67	217	19	14
200	～	220	20	～	22	160	0	79							19	53	75	235		
200	～	220	20	～	22	170	0	79							23	59	85	255		
200	～	220	20	～	22	180	0	79							27	66	96	276	30	
200	～	220	20	～	22	190	0	79							31	73	107	297		
200	～	220	20	～	22	200	0	79							34	80	117	317		
200	～	220	20	～	22	210	0	79							37	85	125	335	52	58
200	～	220	20	～	22	220	0	79							40	94	137	357		
200	～	220	20	～	22	230	0	79						2	40	104	149	379		
200	～	220	20	～	22	240	0	79						3	44	110	160	400	77	
200	～	220	20	～	22	250	0	79						4	48	116	171	421		
200	～	220	20	～	22	260	0	79						6	50	122	181	441		
200	～	220	20	～	22	270	0	79						8	52	130	193	463	99	
200	～	220	20	～	22	280	0	79						9	57	143	212	492		
200	～	220	20	～	22	290	0	79						11	62	155	231	521		
200	～	220	20	～	22	300	0	79						12	66	167	248	548		
200	～	220	20	～	22	310	0	79						14	70	177	264	574		
200	～	220	20	～	22	320	0	79						15	73	188	279	599		
220	～	240	22	～	24	10	0	79									3	13		0
220	～	240	22	～	24	20	0	79									3	23		
220	～	240	22	～	24	30	0	79									3	33	-1	
220	～	240	22	～	24	40	0	79								2	5	45		
220	～	240	22	～	24	50	0	79								5	8	58		-1
220	～	240	22	～	24	60	0	79								12	15	75	-2	
220	～	240	22	～	24	70	0	79								18	21	91		
220	～	240	22	～	24	80	0	79							2	23	28	108		
220	～	240	22	～	24	90	0	79							6	27	36	126	4	-1
220	～	240	22	～	24	100	0	79							10	32	45	145		
220	～	240	22	～	24	110	0	79							12	38	53	163		
220	～	240	22	～	24	120	0	79							17	41	61	181	10	
220	～	240	22	～	24	130	0	79							21	44	68	198		
220	～	240	22	～	24	140	0	79							24	51	78	218		
220	～	240	22	～	24	150	0	79						1	27	57	88	238	24	
220	～	240	22	～	24	160	0	79						2	32	65	102	262		
220	～	240	22	～	24	170	0	79						4	35	73	115	285		
220	～	240	22	～	24	180	0	79						6	37	80	126	306	48	53
220	～	240	22	～	24	190	0	79						8	39	88	138	328		
220	～	240	22	～	24	200	0	79						10	40	99	152	352		
220	～	240	22	～	24	210	0	79						11	44	107	165	375	72	
220	～	240	22	～	24	220	0	79						13	48	114	178	398		
220	～	240	22	～	24	230	0	79						16	51	120	190	420		
220	～	240	22	～	24	240	0	79						19	53	128	203	443	96	
220	～	240	22	～	24	250	0	79						21	58	142	224	474		
220	～	240	22	～	24	260	0	79						23	64	155	245	505		
220	～	240	22	～	24	270	0	79						25	68	169	265	535		
220	～	240	22	～	24	280	0	79						26	73	181	283	563		
220	～	240	22	～	24	290	0	79						28	77	192	300	590		
240	～	260	24	～	26	10	0	79									3	13		0
240	～	260	24	～	26	20	0	79									3	23		0
240	～	260	24	～	26	30	0	79									3	33	-1	
240	～	260	24	～	26	40	0	79								5	8	48		
240	～	260	24	～	26	50	0	79								10	13	63		
240	～	260	24	～	26	60	0	79							2	16	21	81	-2	
240	～	260	24	～	26	70	0	79							4	21	28	98		
240	～	260	24	～	26	80	0	79							9	26	38	118		1
240	～	260	24	～	26	90	0	79							13	31	47	137	6	
240	～	260	24	～	26	100	0	79							16	38	57	157		6
240	～	260	24	～	26	110	0	79							21	42	66	176		11
240	～	260	24	～	26	120	0	79						3	23	46	75	195	18	
240	～	260	24	～	26	130	0	79						5	26	53	87	217		
240	～	260	24	～	26	140	0	79						6	31	60	100	240		
240	～	260	24	～	26	150	0	79						9	34	70	116	266	35	
240	～	260	24	～	26	160	0	79						12	37	78	130	290		57
240	～	260	24	～	26	170	0	79						14	40	86	143	313		
240	～	260	24	～	26	180	0	79						17	41	98	159	339	65	
240	～	260	24	～	26	190	0	79						19	45	107	174	364		
240	～	260	24	～	26	200	0	79						22	49	115	189	389		
240	～	260	24	～	26	210	0	79						26	52	122	203	413	95	
240	～	260	24	～	26	220	0	79						29	56	131	219	439		
240	～	260	24	～	26	230	0	79						31	62	147	243	473		
240	～	260	24	～	26	240	0	79						34	67	162	266	506	145	
240	～	260	24	～	26	250	0	79						36	73	176	288	538		
240	～	260	24	～	26	260	0	79						38	78	189	308	568		
240	～	260	24	～	26	270	0	79					1	40	82	201	327	597		
260	～	280	26	～	28	10	0	79									4	14		0
260	～	280	26	～	28	20	0	79									4	24		0
260	～	280	26	～	28	30	0	79								2	6	36	0	
260	～	280	26	～	28	40	0	79								7	11	51		1
260	～	280	26	～	28	50	0	79							2	13	19	69		
260	～	280	26	～	28	60	0	79							5	18	27	87	-2	-4
260	～	280	26	～	28	70	0	79							9	25	38	108		-6
260	～	280	26	～	28	80	0	79							14	29	47	127		
260	～	280	26	～	28	90	0	79						1	17	38	60	150	9	7
260	～	280	26	～	28	100	0	79						4	21	42	71	171		
260	～	280	26	～	28	110	0	79						7	24	46	81	191		21
260	～	280	26	～	28	120	0	79						9	27	55	95	215	22	
260	～	280	26																	

安全率の設定:1.00

帯底圧力 (kPa)			帯底圧力 (msw)			高圧下 時間(min)	He(%)	N2(%)	空気呼吸 減圧速度80kPa/min				空気呼吸 減圧速度80kPa/min				減圧時間	総業務 時間	別表1 差	別表2 差
を 超え		以下	を 超え	～	以下				240	210	180	150	120	90	60	30				
260	～	280	26	～	28	180	0	79					1	28	48	113	194	374	84	
260	～	280	26	～	28	190	0	79					3	30	52	121	210	400		
260	～	280	26	～	28	200	0	79					5	32	57	131	229	429		
260	～	280	26	～	28	210	0	79					6	34	64	148	256	466	131	
260	～	280	26	～	28	220	0	79					7	36	70	165	282	502		
260	～	280	26	～	28	230	0	79					9	37	76	180	306	536		
260	～	280	26	～	28	240	0	79					10	40	81	194	329	569		
280	～	300	28	～	30	10	0	79									4	14		0
280	～	300	28	～	30	20	0	79									4	24		0
280	～	300	28	～	30	30	0	79								4	8	38	-1	
280	～	300	28	～	30	40	0	79							1	9	14	54		
280	～	300	28	～	30	50	0	79							4	16	24	74	-4	
280	～	300	28	～	30	60	0	79							8	22	34	94	-3	-2
280	～	300	28	～	30	70	0	79						1	14	27	46	116		
280	～	300	28	～	30	80	0	79						3	17	35	59	139		
280	～	300	28	～	30	90	0	79						6	21	41	72	162	4	
280	～	300	28	～	30	100	0	79						10	24	45	83	183		
280	～	300	28	～	30	110	0	79						13	27	54	98	208		
280	～	300	28	～	30	120	0	79						16	33	63	116	236	24	
280	～	300	28	～	30	130	0	79					1	20	36	74	135	265		37
280	～	300	28	～	30	140	0	79					3	22	39	84	152	292		
280	～	300	28	～	30	150	0	79					4	24	42	97	171	321	64	
280	～	300	28	～	30	160	0	79					6	27	47	108	192	352		
280	～	300	28	～	30	170	0	79					9	30	51	118	212	382		
280	～	300	28	～	30	180	0	79					11	32	55	127	229	409	105	
280	～	300	28	～	30	190	0	79					13	35	62	144	258	448		
280	～	300	28	～	30	200	0	79					14	37	70	162	287	487		
280	～	300	28	～	30	210	0	79					16	38	77	179	314	524	169	
280	～	300	28	～	30	220	0	79					19	41	81	195	340	560		
280	～	300	28	～	30	230	0	79					22	44	86	209	365	595		
300	～	320	30	～	32	10	0	79									4	14		0
300	～	320	30	～	32	20	0	79									4	24		
300	～	320	30	～	32	30	0	79								6	10	40	-3	-2
300	～	320	30	～	32	40	0	79							3	11	18	58		-8
300	～	320	30	～	32	50	0	79							7	18	29	79		
300	～	320	30	～	32	60	0	79						2	11	25	42	102	-5	
300	～	320	30	～	32	70	0	79						4	16	31	55	125		
300	～	320	30	～	32	80	0	79						8	19	39	70	150		
300	～	320	30	～	32	90	0	79						12	23	45	84	174	5	
300	～	320	30	～	32	100	0	79						15	27	53	99	199		3
300	～	320	30	～	32	110	0	79					2	18	32	62	118	228		
300	～	320	30	～	32	120	0	79					5	20	37	74	140	260	36	33
300	～	320	30	～	32	130	0	79					7	23	40	85	159	289		
300	～	320	30	～	32	140	0	79					9	25	43	99	180	320		
300	～	320	30	～	32	150	0	79					12	28	48	111	203	353	79	
300	～	320	30	～	32	160	0	79					15	31	53	121	224	384		
300	～	320	30	～	32	170	0	79					17	34	59	132	246	416		
300	～	320	30	～	32	180	0	79					20	36	67	153	280	460	141	
300	～	320	30	～	32	190	0	79					22	38	75	172	311	501		
300	～	320	30	～	32	200	0	79					26	40	80	190	340	540		
300	～	320	30	～	32	210	0	79				2	27	44	85	206	368	578		
320	～	340	32	～	34	10	0	79									4	14		0
320	～	340	32	～	34	20	0	79								1	5	25		
320	～	340	32	～	34	30	0	79							1	7	12	42	-5	
320	～	340	32	～	34	40	0	79							5	14	23	63		
320	～	340	32	～	34	50	0	79						2	8	21	35	85		
320	～	340	32	～	34	60	0	79						4	14	27	49	109	-6	-4
320	～	340	32	～	34	70	0	79						7	18	36	65	135		
320	～	340	32	～	34	80	0	79						13	22	42	81	161		
320	～	340	32	～	34	90	0	79					2	15	26	50	97	187	-2	
320	～	340	32	～	34	100	0	79					5	17	32	58	116	216		
320	～	340	32	～	34	110	0	79					8	20	36	73	141	251		
320	～	340	32	～	34	120	0	79					11	23	40	84	162	282	34	
320	～	340	32	～	34	130	0	79					13	25	44	99	185	315		
320	～	340	32	～	34	140	0	79					17	29	49	112	211	351		
320	～	340	32	～	34	150	0	79				1	19	33	53	123	233	383	87	
320	～	340	32	～	34	160	0	79				2	21	36	61	138	262	422		
320	～	340	32	～	34	170	0	79				3	23	38	70	160	298	468		
320	～	340	32	～	34	180	0	79				6	25	38	79	181	333	513	173	
320	～	340	32	～	34	190	0	79				8	27	43	83	200	365	555		
320	～	340	32	～	34	200	0	79				10	29	47	91	215	396	596		
340	～	360	34	～	36	10	0	79									5	15		
340	～	360	34	～	36	20	0	79								2	7	27		
340	～	360	34	～	36	30	0	79							2	8	15	45	-7	
340	～	360	34	～	36	40	0	79							7	16	28	68		
340	～	360	34	～	36	50	0	79						4	10	23	42	92		
340	～	360	34	～	36	60	0	79						7	16	30	58	118	-7	
340	～	360	34	～	36	70	0	79					1	11	20	40	77	147		
340	～	360	34	～	36	80	0	79					3	15	24	46	93	173		
340	～	360	34	～	36	90	0	79					6	16	30	56	113	203	0	-4
340	～	360	34	～	36	100	0	79					10	20	35	69	139	239		
340	～	360	34	～	36	110	0	79					13	23	39	82	162	272		12
340	～	360	34	～	36	120	0	79				1	15	25	43	97	186	306	42	
340	～	360	34	～	36	130	0	79				4	17	30	49	111	216	346		
340	～	360	34	～	36	140	0	79				5	20	33	54	123	240	380		
340	～	360	34	～	36	150	0	79				7	22	36	63	141	274	424	113	
340	～	360	34	～	36	160	0	79				9	23	39	72	165	313	473		
340	～	360	34	～	36	170	0	79				12	26	41	80	187	351	521		
340	～	360	34	～	36	180	0	79				14	29	45	85	206	384	564		
360	～																			

安全率の設定:1.00

帯底圧力(kPa)			帯底圧力(msw)			高圧下 時間(min)	He(%)	N2(%)	空気呼吸 減圧速度80kPa/min				空気呼吸 減圧速度80kPa/min				減圧時間	総業務 時間	別表1 差	別表2 差
を超え		以下	を超え		以下				240	210	180	150	120	90	60	30				
360	～	380	36	～	38	80	0	79					7	16	26	52	106	186		
360	～	380	36	～	38	90	0	79					11	19	33	63	131	221	4	
360	～	380	36	～	38	100	0	79				1	14	22	38	79	159	259		
360	～	380	36	～	38	110	0	79				4	15	25	42	94	185	295		
360	～	380	36	～	38	120	0	79				7	18	29	48	110	217	337	62	
360	～	380	36	～	38	130	0	79				9	20	33	54	122	243	373		
360	～	380	36	～	38	140	0	79				11	22	37	63	140	278	418		
360	～	380	36	～	38	150	0	79				14	24	38	74	166	321	471	150	
360	～	380	36	～	38	160	0	79				17	27	41	81	189	360	520		
360	～	380	36	～	38	170	0	79			1	19	30	46	88	209	398	568		
380	～	400	38	～	40	10	0	79								5	5	15		
380	～	400	38	～	40	20	0	79								5	10	30		2
380	～	400	38	～	40	30	0	79							6	9	20	50	-10	
380	～	400	38	～	40	40	0	79						4	8	19	36	76		
380	～	400	38	～	40	50	0	79					2	6	15	27	55	105		
380	～	400	38	～	40	60	0	79					4	10	19	38	76	136	-6	
380	～	400	38	～	40	70	0	79					7	15	24	45	96	166		
380	～	400	38	～	40	80	0	79				1	10	17	30	56	119	199		-9
380	～	400	38	～	40	90	0	79				3	13	21	37	72	151	241	11	
380	～	400	38	～	40	100	0	79				6	14	25	41	87	178	278		17
380	～	400	38	～	40	110	0	79				9	17	28	47	105	211	321		
380	～	400	38	～	40	120	0	79				12	20	32	53	120	242	362	81	
380	～	400	38	～	40	130	0	79				14	22	36	62	136	275	405		
380	～	400	38	～	40	140	0	79			2	16	24	39	73	165	324	464		
380	～	400	38	～	40	150	0	79			4	18	28	41	82	190	368	518		
380	～	400	38	～	40	160	0	79			5	20	31	46	90	211	408	568		

※ 他減圧表との差については、プラスが増加、マイナスが減少
※ 最大高圧下の時間は、総作業業務時間が600分を超えない範囲で設定(480分+残業120分)

別添資料2 繰返し空気呼吸・空気減圧表

作業時間60分以内、休憩時間60分

減圧速度 80kPa/min

安全率の設定:1.00

帯底圧力 (kPa)	(msw)	高圧下 時間(min)	He(%)	N2(%)	空気呼吸 減圧速度8kPa/min				空気呼吸 減圧速度8kPa/min				減圧時間	総業務 時間
					240	210	180	150	120	90	60	30		
1回目作業	100	10	60	0	79								1	61
1回目休憩			60	0	79								0	121
2回目作業	100	10	60	0	79								1	182
2回目休憩			60	0	79								0	242
3回目作業	100	10	60	0	79								1	303
3回目休憩			60	0	79								0	363
4回目作業	100	10	60	0	79								1	424
4回目休憩			60	0	79								0	484
5回目作業	100	10	60	0	79								1	545
1回目作業	200	20	60	0	79							1	4	64
1回目休憩			60	0	79								0	124
2回目作業	200	20	60	0	79							9	12	196
2回目休憩			60	0	79								0	256
3回目作業	200	20	60	0	79							14	17	333
3回目休憩			60	0	79								0	393
4回目作業	200	20	60	0	79							16	19	472
1回目作業	300	30	60	0	79						8	22	34	94
1回目休憩			60	0	79								0	154
2回目作業	300	30	60	0	79						15	47	66	280
2回目休憩			60	0	79								0	340
3回目作業	300	30	60	0	79						15	84	103	503
1回目作業	400	40	60	0	79				4	10	19	38	76	136
1回目休憩			60	0	79								0	196
2回目作業	400	40	60	0	79				4	14	36	100	159	415

別添資料3 空気呼吸・空気減圧表（奨励）

減圧速度 80kPa／min
安全率の設定 180, 150, 120, 90, 60, 30, 0kPa:1.10

帯底圧力 (kPa)			帯底圧力 (msw)			高圧下 時間(min)	He(%)	N2(%)	空気呼吸 減圧速度80kPa/min				空気呼吸 減圧速度80kPa/min				減圧時間	総業務 時間	別表1 差	別表2 差
を超え		以下	を超え		以下				240	210	180	150	120	90	60	30				
80	～	100	8	～	10	10	0	79									1	11		
80	～	100	8	～	10	20	0	79									1	21		
80	～	100	8	～	10	30	0	79									1	31		
80	～	100	8	～	10	40	0	79									1	41		
80	～	100	8	～	10	50	0	79									1	51		
80	～	100	8	～	10	60	0	79									1	61		
80	～	100	8	～	10	70	0	79									1	71		
80	～	100	8	～	10	80	0	79									1	81		
80	～	100	8	～	10	90	0	79									1	91		
80	～	100	8	～	10	100	0	79									1	101		
80	～	100	8	～	10	110	0	79									1	111		
80	～	100	8	～	10	120	0	79									1	121		
80	～	100	8	～	10	130	0	79									1	131		
80	～	100	8	～	10	140	0	79									1	141		
80	～	100	8	～	10	150	0	79									1	151		
80	～	100	8	～	10	160	0	79									1	161		
80	～	100	8	～	10	170	0	79									1	171		
80	～	100	8	～	10	180	0	79									1	181		
80	～	100	8	～	10	190	0	79									1	191		
80	～	100	8	～	10	200	0	79									1	201		
80	～	100	8	～	10	210	0	79									1	211		
80	～	100	8	～	10	220	0	79									1	221		
80	～	100	8	～	10	230	0	79									1	231		
80	～	100	8	～	10	240	0	79									1	241		
80	～	100	8	～	10	250	0	79								1	2	252		
80	～	100	8	～	10	260	0	79								3	4	264		
80	～	100	8	～	10	270	0	79								5	6	276		
80	～	100	8	～	10	280	0	79								6	7	287		
80	～	100	8	～	10	290	0	79								7	8	298		
80	～	100	8	～	10	300	0	79								9	10	310		
80	～	100	8	～	10	310	0	79								10	11	321		
80	～	100	8	～	10	320	0	79								11	12	332		
80	～	100	8	～	10	330	0	79								14	15	345		
80	～	100	8	～	10	340	0	79								17	18	358		
80	～	100	8	～	10	350	0	79								21	22	372		
80	～	100	8	～	10	360	0	79								25	26	386		
80	～	100	8	～	10	370	0	79								29	30	400		
80	～	100	8	～	10	380	0	79								32	33	413		
80	～	100	8	～	10	390	0	79								35	36	426		
80	～	100	8	～	10	400	0	79								38	39	439		
80	～	100	8	～	10	410	0	79								41	42	452		
80	～	100	8	～	10	420	0	79								44	45	465		
80	～	100	8	～	10	430	0	79								49	50	480		
80	～	100	8	～	10	440	0	79								53	54	494		
80	～	100	8	～	10	450	0	79								57	58	508		
80	～	100	8	～	10	460	0	79								61	62	522		
80	～	100	8	～	10	470	0	79								65	66	536		
80	～	100	8	～	10	480	0	79								68	69	549		
80	～	100	8	～	10	490	0	79								72	73	563		
80	～	100	8	～	10	500	0	79								75	76	576		
80	～	100	8	～	10	510	0	79								78	79	589		
100	～	120	10	～	12	10	0	79									2	12		0
100	～	120	10	～	12	20	0	79									2	22		
100	～	120	10	～	12	30	0	79									2	32	-1	0
100	～	120	10	～	12	40	0	79									2	42		
100	～	120	10	～	12	50	0	79									2	52		
100	～	120	10	～	12	60	0	79									2	62	-1	0
100	～	120	10	～	12	70	0	79									2	72		
100	～	120	10	～	12	80	0	79									2	82		
100	～	120	10	～	12	90	0	79									2	92	-1	0
100	～	120	10	～	12	100	0	79									2	102		
100	～	120	10	～	12	110	0	79									2	112		
100	～	120	10	～	12	120	0	79									2	122	-1	0
100	～	120	10	～	12	130	0	79									2	132		
100	～	120	10	～	12	140	0	79								1	3	143		
100	～	120	10	～	12	150	0	79								4	6	156	2	
100	～	120	10	～	12	160	0	79								6	8	168		
100	～	120	10	～	12	170	0	79								9	11	181		
100	～	120	10	～	12	180	0	79								12	14	194	9	9
100	～	120	10	～	12	190	0	79								16	18	208		
100	～	120	10	～	12	200	0	79								19	21	221		
100	～	120	10	～	12	210	0	79								22	24	234	18	
100	～	120	10	～	12	220	0	79								24	26	246		
100	～	120	10	～	12	230	0	79								27	29	259		
100	～	120	10	～	12	240	0	79								29	31	271	24	24
100	～	120	10	～	12	250	0	79								33	35	285		
100	～	120	10	～	12	260	0	79								36	38	298		
100	～	120	10	～	12	270	0	79								42	44	314	37	
100	～	120	10	～	12	280	0	79								48	50	330		
100	～	120	10	～	12	290	0	79								53	55	345		
100	～	120	10	～	12	300	0	79								59	61	361	53	
100	～	120	10	～	12	310	0	79								64	66	376		
100	～	120	10	～	12	320	0	79								68	70	390		
100	～	120	10	～	12	330	0	79								73	75	405	67	
100	～	120	10	～	12	340	0	79								79	81	421		
100	～	120	10	～	12	350	0	79								86	88	438		
100	～	120	10	～	12	360	0	79								92	94	454	85	85
100	～	120	10	～	12	370	0	79								97	99	469		
100	～	120	10	～	12	380	0	79								103	105	485		

安全率の設定 180, 150, 120, 90, 60, 30, 0kPa:1.10

帯底圧力 (kPa)			帯底圧力 (msw)			高压下 時間(min)	He(%)	N2(%)	空気呼吸 減圧速度80kPa/min				空気呼吸 減圧速度80kPa/min				減圧時間	総業務 時間	別表1 差	別表2 差
を超え		以下	を超え		以下				240	210	180	150	120	90	60	30				
100	～	120	10	～	12	390	0	79						108	110	500				
100	～	120	10	～	12	400	0	79						113	115	515				
100	～	120	10	～	12	410	0	79						117	119	529				
100	～	120	10	～	12	420	0	79						128	130	550				
100	～	120	10	～	12	430	0	79						139	141	571				
100	～	120	10	～	12	440	0	79						150	152	592				
120	～	140	12	～	14	10	0	79							2	12		0		
120	～	140	12	～	14	20	0	79							2	22				
120	～	140	12	～	14	30	0	79							2	32	-1	0		
120	～	140	12	～	14	40	0	79							2	42				
120	～	140	12	～	14	50	0	79							2	52				
120	～	140	12	～	14	60	0	79							2	62	-1	0		
120	～	140	12	～	14	70	0	79							2	72				
120	～	140	12	～	14	80	0	79							2	82				
120	～	140	12	～	14	90	0	79						1	3	93	0	1		
120	～	140	12	～	14	100	0	79						4	6	106				
120	～	140	12	～	14	110	0	79						7	9	119				
120	～	140	12	～	14	120	0	79						11	13	133	8	7		
120	～	140	12	～	14	130	0	79						15	17	147				
120	～	140	12	～	14	140	0	79						18	20	160				
120	～	140	12	～	14	150	0	79						24	26	176	19	18		
120	～	140	12	～	14	160	0	79						29	31	191				
120	～	140	12	～	14	170	0	79						33	35	205				
120	～	140	12	～	14	180	0	79						37	39	219	31	30		
120	～	140	12	～	14	190	0	79						40	42	232				
120	～	140	12	～	14	200	0	79						44	46	246				
120	～	140	12	～	14	210	0	79						49	51	261	41	40		
120	～	140	12	～	14	220	0	79						55	57	277				
120	～	140	12	～	14	230	0	79						63	65	295				
120	～	140	12	～	14	240	0	79						71	73	313	61	61		
120	～	140	12	～	14	250	0	79						78	80	330				
120	～	140	12	～	14	260	0	79						85	87	347				
120	～	140	12	～	14	270	0	79						91	93	363	81			
120	～	140	12	～	14	280	0	79					2	98	102	382				
120	～	140	12	～	14	290	0	79					4	105	111	401				
120	～	140	12	～	14	300	0	79					5	112	119	419	107	105		
120	～	140	12	～	14	310	0	79					6	119	127	437				
120	～	140	12	～	14	320	0	79					8	125	135	455				
120	～	140	12	～	14	330	0	79					9	131	142	472	128			
120	～	140	12	～	14	340	0	79					10	137	149	489				
120	～	140	12	～	14	350	0	79					11	151	164	514				
120	～	140	12	～	14	360	0	79					12	165	179	539				
120	～	140	12	～	14	370	0	79					15	177	194	564				
120	～	140	12	～	14	380	0	79					17	189	208	588				
140	～	160	14	～	16	10	0	79							2	12		0		
140	～	160	14	～	16	20	0	79							2	22				
140	～	160	14	～	16	30	0	79							2	32	-1	0		
140	～	160	14	～	16	40	0	79							2	42				
140	～	160	14	～	16	50	0	79							2	52		0		
140	～	160	14	～	16	60	0	79							2	62	-1			
140	～	160	14	～	16	70	0	79						2	4	74		2		
140	～	160	14	～	16	80	0	79						7	9	89				
140	～	160	14	～	16	90	0	79						11	13	103	8	8		
140	～	160	14	～	16	100	0	79						16	18	118				
140	～	160	14	～	16	110	0	79						21	23	133				
140	～	160	14	～	16	120	0	79						26	28	148	21	20		
140	～	160	14	～	16	130	0	79						33	35	165				
140	～	160	14	～	16	140	0	79						39	41	181				
140	～	160	14	～	16	150	0	79						44	46	196	37	35		
140	～	160	14	～	16	160	0	79					1	48	51	211				
140	～	160	14	～	16	170	0	79					3	52	57	227				
140	～	160	14	～	16	180	0	79					5	58	65	245	54	51		
140	～	160	14	～	16	190	0	79					7	65	74	264				
140	～	160	14	～	16	200	0	79					9	74	85	285				
140	～	160	14	～	16	210	0	79					12	82	96	306	8			

安全率の設定 180, 150, 120, 90, 60, 30, 0kPa:1.10

帯底圧力 (kPa)		帯底圧力 (msw)		高压下 時間(min)	He(%)	N2(%)	空気呼吸 減圧速度80kPa/min				空気呼吸 減圧速度80kPa/min				減圧時間	総業務 時間	別表1 差	別表2 差
を超え	以下	を超え	以下				240	210	180	150	120	90	60	30				
160	～	180	16 ～ 18	160	0	79							16	62	80	240		
160	～	180	16 ～ 18	170	0	79							19	73	94	264		
160	～	180	16 ～ 18	180	0	79							24	81	107	287	80	82
160	～	180	16 ～ 18	190	0	79							28	89	119	309		
160	～	180	16 ～ 18	200	0	79							32	96	130	330		
160	～	180	16 ～ 18	210	0	79							35	108	145	355	110	
160	～	180	16 ～ 18	220	0	79							38	118	158	378		
160	～	180	16 ～ 18	230	0	79							40	128	170	400		
160	～	180	16 ～ 18	240	0	79							43	137	182	422	141	150
160	～	180	16 ～ 18	250	0	79							48	144	194	444		
160	～	180	16 ～ 18	260	0	79							53	164	219	479		
160	～	180	16 ～ 18	270	0	79							57	182	241	511	194	
160	～	180	16 ～ 18	280	0	79							62	198	262	542		
160	～	180	16 ～ 18	290	0	79						1	68	213	284	574		
180	～	200	18 ～ 20	10	0	79									3	13		0
180	～	200	18 ～ 20	20	0	79									3	23		
180	～	200	18 ～ 20	30	0	79									3	33	-1	
180	～	200	18 ～ 20	40	0	79								2	5	45		
180	～	200	18 ～ 20	50	0	79								5	8	58		5
180	～	200	18 ～ 20	60	0	79								12	15	75	4	
180	～	200	18 ～ 20	70	0	79								18	21	91		
180	～	200	18 ～ 20	80	0	79							1	26	30	110		
180	～	200	18 ～ 20	90	0	79							5	30	38	128	19	
180	～	200	18 ～ 20	100	0	79							8	38	49	149		
180	～	200	18 ～ 20	110	0	79							11	45	59	169		
180	～	200	18 ～ 20	120	0	79							16	49	68	188	43	
180	～	200	18 ～ 20	130	0	79							20	54	77	207		
180	～	200	18 ～ 20	140	0	79							24	62	89	229		
180	～	200	18 ～ 20	150	0	79							28	73	104	254	72	
180	～	200	18 ～ 20	160	0	79							34	83	120	280		
180	～	200	18 ～ 20	170	0	79							39	92	134	304		
180	～	200	18 ～ 20	180	0	79						1	42	103	149	329	105	
180	～	200	18 ～ 20	190	0	79						4	44	116	167	357		
180	～	200	18 ～ 20	200	0	79						6	46	128	183	383		
180	～	200	18 ～ 20	210	0	79						7	51	137	198	408	145	
180	～	200	18 ～ 20	220	0	79						8	56	148	215	435		
180	～	200	18 ～ 20	230	0	79						11	59	172	245	475		
180	～	200	18 ～ 20	240	0	79						14	63	192	272	512	209	
180	～	200	18 ～ 20	250	0	79						17	70	210	300	550		
180	～	200	18 ～ 20	260	0	79						19	76	226	324	584		
200	～	220	20 ～ 22	10	0	79									3	13		
200	～	220	20 ～ 22	20	0	79									3	23		
200	～	220	20 ～ 22	30	0	79									3	33	-1	0
200	～	220	20 ～ 22	40	0	79								5	8	48		
200	～	220	20 ～ 22	50	0	79								11	14	64		
200	～	220	20 ～ 22	60	0	79							1	18	22	82	8	12
200	～	220	20 ～ 22	70	0	79							3	26	32	102		
200	～	220	20 ～ 22	80	0	79							8	31	42	122		
200	～	220	20 ～ 22	90	0	79							13	39	55	145	29	
200	～	220	20 ～ 22	100	0	79							17	46	66	166		35
200	～	220	20 ～ 22	110	0	79							23	50	76	186		
200	～	220	20 ～ 22	120	0	79						1	27	58	89	209	54	47
200	～	220	20 ～ 22	130	0	79						3	30	69	105	235		
200	～	220	20 ～ 22	140	0	79						5	36	81	125	265		
200	～	220	20 ～ 22	150	0	79						8	40	92	143	293	95	90
200	～	220	20 ～ 22	160	0	79						11	43	105	162	322		
200	～	220	20 ～ 22	170	0	79						13	46	119	181	351		
200	～	220	20 ～ 22	180	0	79						16	49	132	200	380	134	
200	～	220	20 ～ 22	190	0	79						18	55	141	217	407		
200	～	220	20 ～ 22	200	0	79						22	59	163	247	447		
200	～	220	20 ～ 22	210	0	79						26	63	188	280	490	207	213
200	～	220	20 ～ 22	220	0	79						29	71	208	311	531		
200	～	220	20 ～ 22	230	0	79						32	78	226	339	569		
220	～	240	22 ～ 24	10	0	79									3	13		0
220	～	240	22 ～ 24	20	0	79									3	23		
220	～	240	22 ～ 24	30	0	79								3	6	36	2	
220	～	240	22 ～ 24	40	0	79								8	11	51		
220	～	240	22 ～ 24	50	0	79							2	16	21	71		12
220	～	240	22 ～ 24	60	0	79							5	23	31	91	14	
220	～	240	22 ～ 24	70	0	79							10	30	43	113		
220	～	240	22 ～ 24	80	0	79							16	38	57	137		
220	～	240	22 ～ 24	90	0	79							21	46	70	160	38	33
220	～	240	22 ～ 24	100	0	79						4	25	51	83	183		
220	～	240	22 ～ 24	110	0	79						7	28	61	99	209		
220	～	240	22 ～ 24	120	0	79						9	34	74	120	240	69	
220	～	240	22 ～ 24	130	0	79						12	39	87	141	271		
220	～	240	22 ～ 24	140	0	79						17	42	99	161	301		
220	～	240	22 ～ 24	150	0	79						20	46	116	185	335	121	
220	～	240	22 ～ 24	160	0	79						23	49	131	206	366		
220	～	240	22 ～ 24	170	0	79						26	56	141	226	396		
220	～	240	22 ～ 24	180	0	79						32	60	166	261	441	183	188
220	～	240	22 ～ 24	190	0	79					1	35	67	192	298	488		
220	～	240	22 ～ 24	200	0	79					3	38	75	215	334	534		
220	～	240	22 ～ 24	210	0	79					4	41	83	235	366	576	273	
240	～	260	24 ～ 26	10	0	79									3	13		0
240	～	260	24 ～ 26	20	0	79									3	23		0
240	～	260	24 ～ 26	30	0	79								5	8	38	4	
240	～	260	24 ～ 26	40	0	79							2	11	16	56		
240	～	260	24 ～ 26	50	0	79							5	19	27	77		
240	～	260	24 ～ 26	60	0	79							10	27	40	100	17	
240	～	260	24 ～ 26	70	0	79						1	16	35	55	125		
240	～	260	24 ～ 26	80	0	79						3	20	45	71	151		34

安全率の設定 180, 150, 120, 90, 60, 30, 0kPa:1.10

帯底圧力 (kPa)		帯底圧力 (msw)		高压下 時間(min)	He(%)	N2(%)	空気呼吸 減圧速度80kPa/min				空気呼吸 減圧速度80kPa/min				減圧時間	総業務 時間	別表1 差	別表2 差
を超え	以下	を超え	以下				240	210	180	150	120	90	60	30				
240	～	260	24 ～ 26	90	0	79						7	25	51	86	176	45	
240	～	260	24 ～ 26	100	0	79						11	29	61	104	204		53
240	～	260	24 ～ 26	110	0	79						14	35	76	128	238		73
240	～	260	24 ～ 26	120	0	79						19	40	90	152	272	95	
240	～	260	24 ～ 26	130	0	79						24	44	105	176	306		
240	～	260	24 ～ 26	140	0	79					2	26	48	124	203	343		
240	～	260	24 ～ 26	150	0	79					4	28	55	137	227	377	146	
240	～	260	24 ～ 26	160	0	79					6	33	60	159	261	421		188
240	～	260	24 ～ 26	170	0	79					9	37	66	191	306	476		
240	～	260	24 ～ 26	180	0	79					12	39	77	216	347	527	253	
240	～	260	24 ～ 26	190	0	79					14	42	85	238	382	572		
260	～	280	26 ～ 28	10	0	79									4	14		0
260	～	280	26 ～ 28	20	0	79								1	5	25		1
260	～	280	26 ～ 28	30	0	79								7	11	41	5	
260	～	280	26 ～ 28	40	0	79							4	14	22	62		12
260	～	280	26 ～ 28	50	0	79							8	23	35	85		
260	～	280	26 ～ 28	60	0	79						2	14	31	51	111	22	20
260	～	280	26 ～ 28	70	0	79						5	19	42	70	140		26
260	～	280	26 ～ 28	80	0	79						9	25	49	87	167		
260	～	280	26 ～ 28	90	0	79						14	29	60	107	197	56	54
260	～	280	26 ～ 28	100	0	79						18	35	75	132	232		
260	～	280	26 ～ 28	110	0	79					3	22	41	91	161	271		101
260	～	280	26 ～ 28	120	0	79					6	25	45	110	190	310	117	
260	～	280	26 ～ 28	130	0	79					8	28	49	129	218	348		
260	～	280	26 ～ 28	140	0	79					11	31	57	143	246	386		172
260	～	280	26 ～ 28	150	0	79					14	36	62	176	292	442	198	
260	～	280	26 ～ 28	160	0	79					18	39	73	207	341	501		
260	～	280	26 ～ 28	170	0	79					21	42	84	232	383	553		
260	～	280	26 ～ 28	180	0	79					23	45	92	254	418	598	308	
280	～	300	28 ～ 30	10	0	79									4	14		0
280	～	300	28 ～ 30	20	0	79								2	6	26		2
280	～	300	28 ～ 30	30	0	79							1	9	14	44	5	
280	～	300	28 ～ 30	40	0	79							7	17	28	68		
280	～	300	28 ～ 30	50	0	79						3	10	27	44	94		16
280	～	300	28 ～ 30	60	0	79						5	18	36	63	123	26	27
280	～	300	28 ～ 30	70	0	79						10	22	47	83	153		
280	～	300	28 ～ 30	80	0	79					1	15	27	56	103	183		
280	～	300	28 ～ 30	90	0	79					3	18	34	72	131	221	63	
280	～	300	28 ～ 30	100	0	79					7	22	40	90	163	263		
280	～	300	28 ～ 30	110	0	79					10	25	46	110	195	305		
280	～	300	28 ～ 30	120	0	79					13	28	51	130	226	346	134	
280	～	300	28 ～ 30	130	0	79					17	33	58	146	258	388		160
280	～	300	28 ～ 30	140	0	79					21	37	66	186	314	454		
280	～	300	28 ～ 30	150	0	79				2	23	41	78	217	365	515	258	
280	～	300	28 ～ 30	160	0	79				3	26	44	89	244	410	570		
300	～	320	30 ～ 32	10	0	79									4	14		0
300	～	320	30 ～ 32	20	0	79								3	7	27		
300	～	320	30 ～ 32	30	0	79							4	9	17	47	4	5
300	～	320	30 ～ 32	40	0	79						1	8	20	33	73		7
300	～	320	30 ～ 32	50	0	79						5	14	30	53	103		
300	～	320	30 ～ 32	60	0	79					1	8	20	42	75	135	28	
300	～	320	30 ～ 32	70	0	79					2	14	26	51	97	167		
300	～	320	30 ～ 32	80	0	79					5	18	30	66	123	203		
300	～	320	30 ～ 32	90	0	79					9	21	40	86	160	250	81	
300	～	320	30 ～ 32	100	0	79					14	25	45	106	194	294		98
300	～	320	30 ～ 32	110	0	79					17	28	50	129	228	338		
300	～	320	30 ～ 32	120	0	79				3	19	34	59	148	267	387	163	160
300	～	320	30 ～ 32	130	0	79				6	22	38	69	192	331	461		
300	～	320	30 ～ 32	140	0	79				8	24	43	81	225	385	525		
300	～	320	30 ～ 32	150	0	79				9	27	46	93	252	431	581	307	
320	～	340	32 ～ 34	10	0	79									4	14		0
320	～	340	32 ～ 34	20	0	79								5	9	29		
320	～	340	32 ～ 34	30	0	79							6	11	21	51	4	
320	～	340	32 ～ 34	40	0	79						4	9	23	40	80		
320	～	340	32 ～ 34	50	0	79					1	7	17	33	62	112		
320	～	340	32 ～ 34	60	0	79					3	11	23	47	88	148	33	35
320	～	340	32 ～ 34	70	0	79					6	16	29	58	113	183		
320	～	340	32 ～ 34	80	0	79					10	19	37	79	149	229		
320	～	340	32 ～ 34	90	0	79				1	15	24	44	98	186	276	87	
320	～	340	32 ～ 34	100	0	79				3	17	28	49	125	226	326		
320	～	340	32 ～ 34	110	0	79				7	19	34	58	145	267	377		
320	～	340	32 ～ 34	120	0	79				10	23	38	69	192	336	456	208	
320	～	340	32 ～ 34	130	0	79				12	26	43	83	227	395	525		
320	～	340	32 ～ 34	140	0	79				16	27	46	95	257	445	585		
340	～	360	34 ～ 36	10	0	79									5	15		
340	～	360	34 ～ 36	20	0	79							1	6	12	32		
340	～	360	34 ～ 36	30	0	79						1	7	14	27	57	5	
340	～	360	34 ～ 36	40	0	79						6	10	27	48	88		
340	～	360	34 ～ 36	50	0	79					3	8	19	39	74	124		
340	～	360	34 ～ 36	60	0	79					6	14	25	51	101	161	36	
340	～	360	34 ～ 36	70	0	79				1	9	18	32	68	133	203		
340	～	360	34 ～ 36	80	0	79				3	13	23	41	91	176	256		
340	～	360	34 ～ 36	90	0	79				5	17	27	48	117	219	309	106	102
340	～	360	34 ～ 36	100	0	79				9	19	32	57	140	262	362		
340	～	360	34 ～ 36	110	0	79				13	23	38	66	185	330	440		180
340	～	360	34 ～ 36	120	0	79				16	26	43	82	224	396	516	252	
340	～	360	34 ～ 36	130	0	79			3	18	28	46	96	258	454	584		
360	～	380	36 ～ 38	10	0	79									5	15		
360	～	380	36 ～ 38	20	0	79							2	7	14	34		
360	～	380	36 ～ 38	30	0	79						2	8	16	31	61	5	4
360	～	380	36 ～ 38	40	0	79					1	7	13	29	55	95		11
360	～	380	36 ～ 38	50	0	79					5	10	20	44	84	134		30

安全率の設定 180, 150, 120, 90, 60, 30, 0kPa:1.10

帯底圧力 (kPa)			帯底圧力 (msw)			高圧下 時間(min)	He(%)	N2(%)	空気呼吸 減圧速度80kPa/min				空気呼吸 減圧速度80kPa/min				減圧時間	総業務 時間	別表1 差	別表2 差
を超え	～	以下	を超え	～	以下				240	210	180	150	120	90	60	30				
360	～	380	36	～	38	60	0	79				2	7	16	28	57	115	175	41	
360	～	380	36	～	38	70	0	79				3	12	20	38	79	157	227		
360	～	380	36	～	38	80	0	79				7	15	26	45	105	203	283		
360	～	380	36	～	38	90	0	79				11	17	30	53	133	249	339	122	
360	～	380	36	～	38	100	0	79			1	14	22	37	62	171	312	412		
360	～	380	36	～	38	110	0	79			4	15	26	42	80	218	390	500		
360	～	380	36	～	38	120	0	79			7	18	28	46	95	255	454	574	299	
380	～	400	38	～	40	10	0	79									5	15		
380	～	400	38	～	40	20	0	79							3	8	16	36		8
380	～	400	38	～	40	30	0	79						4	8	19	36	66	6	
380	～	400	38	～	40	40	0	79					3	7	16	31	62	102		
380	～	400	38	～	40	50	0	79				1	6	13	23	48	96	146		
380	～	400	38	～	40	60	0	79				4	9	18	30	64	130	190	48	
380	～	400	38	～	40	70	0	79				7	14	23	41	91	181	251		
380	～	400	38	～	40	80	0	79			1	10	17	28	48	122	231	311		103
380	～	400	38	～	40	90	0	79			3	14	20	35	59	149	285	375	145	
380	～	400	38	～	40	100	0	79			6	15	25	41	74	205	371	471		210
380	～	400	38	～	40	110	0	79			10	17	27	46	92	246	443	553		

※ 他減圧表との差については、プラスが増加、マイナスが減少
※ 最大高圧下の時間は、総作業業務時間が600分を超えない範囲で設定(480分+残業120分)

別添資料4 空気呼吸・酸素減圧表（奨励）

減圧速度 80kPa／min
安全率の設定 180, 150, 120kPa:1.10 90kPa:1.35 60kPa:1.40 0kPa:1.21

帯底圧力 (kPa)			帯底圧力 (msw)			高圧下 時間(min)	He(%)	N2(%)	空気呼吸 減圧速度80kPa/min				酸素呼吸 減圧速度80kPa/min				減圧時間	総業務 時間	CPTD	別表1 差	別表2 差
を超え		以下	を超え		以下				240	210	180	150	120	90	60	30					
80	～	100	8	～	10	10	0	79								1	11	0			
80	～	100	8	～	10	20	0	79								1	21	0			
80	～	100	8	～	10	30	0	79								1	31	0			
80	～	100	8	～	10	40	0	79								1	41	0			
80	～	100	8	～	10	50	0	79								1	51	0			
80	～	100	8	～	10	60	0	79								1	61	0			
80	～	100	8	～	10	70	0	79								1	71	0			
80	～	100	8	～	10	80	0	79								1	81	0			
80	～	100	8	～	10	90	0	79								1	91	0			
80	～	100	8	～	10	100	0	79								1	101	0			
80	～	100	8	～	10	110	0	79								1	111	0			
80	～	100	8	～	10	120	0	79								1	121	0			
80	～	100	8	～	10	130	0	79								1	131	0			
80	～	100	8	～	10	140	0	79							1	2	142	3			
80	～	100	8	～	10	150	0	79							2	3	153	4			
80	～	100	8	～	10	160	0	79							3	4	164	6			
80	～	100	8	～	10	170	0	79							5	6	176	10			
80	～	100	8	～	10	180	0	79							6	7	187	12			
80	～	100	8	～	10	190	0	79							8	9	199	16			
80	～	100	8	～	10	200	0	79							9	10	210	18			
80	～	100	8	～	10	210	0	79							10	11	221	20			
80	～	100	8	～	10	220	0	79							11	12	232	22			
80	～	100	8	～	10	230	0	79							12	13	243	24			
80	～	100	8	～	10	240	0	79							13	14	254	26			
80	～	100	8	～	10	250	0	79							15	16	266	30			
80	～	100	8	～	10	260	0	79							17	18	278	33			
80	～	100	8	～	10	270	0	79							19	20	290	37			
80	～	100	8	～	10	280	0	79							21	22	302	41			
80	～	100	8	～	10	290	0	79							23	24	314	45			
80	～	100	8	～	10	300	0	79							30	31	331	49			
80	～	100	8	～	10	310	0	79							32	33	343	53			
80	～	100	8	～	10	320	0	79							34	35	355	57			
80	～	100	8	～	10	330	0	79							36	37	367	60			
80	～	100	8	～	10	340	0	79							38	39	379	64			
80	～	100	8	～	10	350	0	79							40	41	391	68			
80	～	100	8	～	10	360	0	79							42	43	403	72			
80	～	100	8	～	10	370	0	79							45	46	416	78			
80	～	100	8	～	10	380	0	79							46	47	427	80			
80	～	100	8	～	10	390	0	79							48	49	439	84			
80	～	100	8	～	10	400	0	79							50	51	451	87			
80	～	100	8	～	10	410	0	79							52	53	463	91			
80	～	100	8	～	10	420	0	79							61	62	482	99			
80	～	100	8	～	10	430	0	79							64	65	495	105			
80	～	100	8	～	10	440	0	79							67	68	508	111			
80	～	100	8	～	10	450	0	79							71	72	522	118			
80	～	100	8	～	10	460	0	79							74	75	535	124			
80	～	100	8	～	10	470	0	79							77	78	548	130			
80	～	100	8	～	10	480	0	79							79	80	560	134			
80	～	100	8	～	10	490	0	79							82	83	573	140			
80	～	100	8	～	10	500	0	79							85	86	586	144			
100	～	120	10	～	12	10	0	79								2	12	0		0	
100	～	120	10	～	12	20	0	79								2	22	0			
100	～	120	10	～	12	30	0	79								2	32	0	-1	0	
100	～	120	10	～	12	40	0	79								2	42	0			
100	～	120	10	～	12	50	0	79								2	52	0			
100	～	120	10	～	12	60	0	79								2	62	0	-1	0	
100	～	120	10	～	12	70	0	79								2	72	0			
100	～	120	10	～	12	80	0	79								2	82	0			
100	～	120	10	～	12	90	0	79									93	3	0	1	
100	～	120	10	～																	

安全率の設定 180, 150, 120kPa:1.10 90kPa:1.35 60kPa:1.40 0kPa:1.21

帯底圧力(kPa)			帯底圧力(msw)			高圧下 時間(min)	He(%)	N2(%)	空気呼吸 減圧速度80kPa/min				酸素呼吸 減圧速度80kPa/min				減圧時間	総業務 時間	CPTD	別表1 差	別表2 差
を超え	以下		を超え	以下					240	210	180	150	120	90	60	30					
160	～	180	16	～	18	110	0	79					7	27		36	146	86			
160	～	180	16	～	18	120	0	79					10	27		39	159	95	24		
160	～	180	16	～	18	130	0	79					12	29		43	173	106			
160	～	180	16	～	18	140	0	79					13	33		48	188	119			
160	～	180	16	～	18	150	0	79					15	36		53	203	131	34	31	
160	～	180	16	～	18	160	0	79					17	45		64	224	146			
160	～	180	16	～	18	170	0	79				1	18	48		69	239	160			
160	～	180	16	～	18	180	0	79				1	20	51		74	254	173	47	49	
160	～	180	16	～	18	190	0	79				2	21	55		80	270	189			
160	～	180	16	～	18	200	0	79				3	22	64		91	291	204			
160	～	180	16	～	18	210	0	79				4	27	65		98	308	220	63		
160	～	180	16	～	18	220	0	79				4	29	68		103	323	233			
160	～	180	16	～	18	230	0	79				5	31	70		108	338	247			
160	～	180	16	～	18	240	0	79				6	32	76		116	356	265	75	84	
160	～	180	16	～	18	250	0	79				7	33	87		129	379	285			
160	～	180	16	～	18	260	0	79				8	35	92		137	397	305			
160	～	180	16	～	18	270	0	79				9	37	96		144	414	322	97		
160	～	180	16	～	18	280	0	79				9	39	106		156	436	339			
160	～	180	16	～	18	290	0	79				10	41	110		163	453	356			
160	～	180	16	～	18	300	0	79				11	42	114		169	469	372	115		
160	～	180	16	～	18	310	0	79				11	49	120		182	492	390			
160	～	180	16	～	18	320	0	79				12	51	123		188	508	406			
160	～	180	16	～	18	330	0	79				13	52	126		193	523	419			
160	～	180	16	～	18	340	0	79				14	54	129		199	539	435			
160	～	180	16	～	18	350	0	79				15	56	132		205	555	450			
160	～	180	16	～	18	360	0	79				16	58	141		217	577	468			
160	～	180	16	～	18	370	0	79				17	59	146		224	594	485			
180	～	200	18	～	20	10	0	79								3	13	2		0	
180	～	200	18	～	20	20	0	79								3	23	5			
180	～	200	18	～	20	30	0	79						1		4	34	12	0		
180	～	200	18	～	20	40	0	79						4		7	47	21			
180	～	200	18	～	20	50	0	79					1	7		11	61	33		8	
180	～	200	18	～	20	60	0	79					2	10		15	75	44	4		
180	～	200	18	～	20	70	0	79					4	13		20	90	58			
180	～	200	18	～	20	80	0	79					6	16		25	105	72			
180	～	200	18	～	20	90	0	79					9	23		35	125	86	16		
180	～	200	18	～	20	100	0	79					11	26		40	140	100			
180	～	200	18	～	20	110	0	79				1	12	28		44	154	113			
180	～	200	18	～	20	120	0	79				1	14	31		49	169	127	24		
180	～	200	18	～	20	130	0	79				2	15	35		55	185	143			
180	～	200	18	～	20	140	0	79				3	17	44		67	207	161			
180	～	200	18	～	20	150	0	79				4	19	47		73	223	178	41		
180	～	200	18	～	20	160	0	79				6	24	47		80	240	196			
180	～	200	18	～	20	170	0	79				7	26	51		87	257	214			
180	～	200	18	～	20	180	0	79				8	27	61		99	279	233	55		
180	～	200	18	～	20	190	0	79				9	28	65		105	295	249			
180	～	200	18	～	20	200	0	79				10	30	68		111	311	265			
180	～	200	18	～	20	210	0	79				11	32	77		123	333	284	70		
180	～	200	18	～	20	220	0	79				13	32	84		132	352	306			
180	～	200	18	～	20	230	0	79				14	35	89		141	371	329			
180	～	200	18	～	20	240	0	79				15	37	100		155	395	351	92		
180	～	200	18	～	20	250	0	79				16	44	101		164	414	374			
180	～	200	18	～	20	260	0	79				17	46	106		172	432	394			

安全率の設定 180, 150, 120kPa:1.10 90kPa:1.35 60kPa:1.40 0kPa:1.21

帯底圧力(kPa)		帯底圧力(msw)		高圧下 時間(min)	He(%)	N2(%)	空気呼吸 減圧速度80kPa/min				酸素呼吸 減圧速度80kPa/min				減圧時間	総業務 時間	CPTD	別表1 差	別表2 差
を 超え	以下	を 超え	以下				240	210	180	150	120	90	60	30					
220	～	240	22 ～ 24	50	0	79				5	10			18	68	56		9	
220	～	240	22 ～ 24	60	0	79				1	6	14		24	84	75	7		
220	～	240	22 ～ 24	70	0	79				2	9	21		35	105	94			
220	～	240	22 ～ 24	80	0	79				3	11	25		42	122	114			
220	～	240	22 ～ 24	90	0	79				5	13	27		48	138	133	16	11	
220	～	240	22 ～ 24	100	0	79				7	14	31		55	155	153			
220	～	240	22 ～ 24	110	0	79				8	16	40		67	177	174			
220	～	240	22 ～ 24	120	0	79				10	23	41		77	197	200	26		
220	～	240	22 ～ 24	130	0	79				12	25	45		85	215	223			
220	～	240	22 ～ 24	140	0	79				14	26	55		98	238	246			
220	～	240	22 ～ 24	150	0	79				16	27	61		107	257	270	43		
220	～	240	22 ～ 24	160	0	79				18	29	65		115	275	293			
220	～	240	22 ～ 24	170	0	79				20	31	74		128	298	316			
220	～	240	22 ～ 24	180	0	79				22	35	78		138	318	343	60	65	
220	～	240	22 ～ 24	190	0	79				24	40	89		156	346	375			
220	～	240	22 ～ 24	200	0	79				30	39	96		168	368	406			
220	～	240	22 ～ 24	210	0	79				32	42	106		183	393	433	90		
220	～	240	22 ～ 24	220	0	79				33	45	112		193	413	459			
220	～	240	22 ～ 24	230	0	79				36	46	117		202	432	485			
220	～	240	22 ～ 24	240	0	79				38	53	124		218	458	513	111		
220	～	240	22 ～ 24	250	0	79				41	55	127		226	476	537			
220	～	240	22 ～ 24	260	0	79				43	58	130		234	494	561			
220	～	240	22 ～ 24	270	0	79				44	61	142		250	520	589			
240	～	260	24 ～ 26	10	0	79								3	13	4		0	
240	～	260	24 ～ 26	20	0	79						1		4	24	13		1	
240	～	260	24 ～ 26	30	0	79					1	5		9	39	30	5		
240	～	260	24 ～ 26	40	0	79					4	8		15	55	48			
240	～	260	24 ～ 26	50	0	79				1	6	12		22	72	70			
240	～	260	24 ～ 26	60	0	79				2	9	19		33	93	90	10		
240	～	260	24 ～ 26	70	0	79				4	10	24		41	111	113			
240	～	260	24 ～ 26	80	0	79				6	13	26		48	128	135		11	
240	～	260	24 ～ 26	90	0	79				9	14	29		55	145	157	14		
240	～	260	24 ～ 26	100	0	79				10	21	35		69	169	182		18	
240	～	260	24 ～ 26	110	0	79				13	22	41		79	189	210		24	
240	～	260	24 ～ 26	120	0	79				15	25	50		93	213	236	36		
240	～	260	24 ～ 26	130	0	79				17	26	56		102	232	261			
240	～	260	24 ～ 26	140	0	79				19	28	62		112	252	289			
240	～	260	24 ～ 26	150	0	79				22	30	71		126	276	315	45		
240	～	260	24 ～ 26	160	0	79				25	36	71		135	295	341		62	
240	～	260	24 ～ 26	170	0	79				32	34	85		154	324	377			
240	～	260	24 ～ 26	180	0	79				34	38	91		166	346	409	72		
240	～	260	24 ～ 26	190	0	79				36	41	104		184	374	443			
240	～	260	24 ～ 26	200	0	79				38	44	109		194	394	471			
240	～	260	24 ～ 26	210	0	79				41	50	112		206	416	503	98		
240	～	260	24 ～ 26	220	0	79				43	53	122		221	441	531			
240	～	260	24 ～ 26	230	0	79				46	55	127		231	461	559			
240	～	260	24 ～ 26	240	0	79				48	59	136		246	486	588	125		
260	～	280	26 ～ 28	10	0	79								4	14	5		0	
260	～	280	26 ～ 28	20	0	79						2		6	26	16		2	
260	～	280	26 ～ 28	30	0	79					3	5		12	42	37	6		
260	～	280	26 ～ 28	40	0	79				1	5	9		19	59	59		9	
260	～	280	26 ～ 28	50	0	79				3	6	14		27	77	83			
260	～	280	26 ～ 28	60	0	79				4	10	21		39	99	106	10	8	
260	～	280	26 ～ 28	70	0	79				7	11	26		48	118	133		4	
260	～	280	26 ～ 28	80	0	79				10	13	28		55	135	156			
260	～	280	26 ～ 28	90	0	79				12	19	34		69	159	182	18	16	
260	～	280	26 ～ 28	100	0	79													

安全率の設定 180, 150, 120kPa:1.10 90kPa:1.35 60kPa:1.40 0kPa:1.21

帯底圧力(kPa)			帯底圧力(msw)			高圧下 時間(min)	He(%)	N2(%)	空気呼吸 減圧速度80kPa/min				酸素呼吸 減圧速度80kPa/min				減圧時間	総業務 時間	CPTD	別表1 差	別表2 差
を 超え	以下		を 超え	以下					240	210	180	150	120	90	60	30					
300	～	320	30	～	32	100	0	79					23	25	51		103	203	271		7
300	～	320	30	～	32	110	0	79					30	24	58		116	226	308		
300	～	320	30	～	32	120	0	79				3	34	30	67		138	258	347	34	31
300	～	320	30	～	32	130	0	79				6	37	33	73		153	283	382		
300	～	320	30	～	32	140	0	79				8	40	37	89		178	318	429		
300	～	320	30	～	32	150	0	79				9	42	42	103		200	350	472	76	
300	～	320	30	～	32	160	0	79				13	46	49	109		221	381	516		
300	～	320	30	～	32	170	0	79				16	49	52	122		243	413	556		
300	～	320	30	～	32	180	0	79				19	52	57	133		265	445	596	126	
320	～	340	32	～	34	10	0	79									4	14	7		0
320	～	340	32	～	34	20	0	79						2	4		10	30	30		
320	～	340	32	～	34	30	0	79					2	4	8		18	48	58	1	
320	～	340	32	～	34	40	0	79					5	6	13		28	68	88		
320	～	340	32	～	34	50	0	79					8	10	21		43	93	121		
320	～	340	32	～	34	60	0	79					11	13	26		54	114	155	-1	1
320	～	340	32	～	34	70	0	79					15	19	31		69	139	187		
320	～	340	32	～	34	80	0	79					19	21	37		81	161	223		
320	～	340	32	～	34	90	0	79				1	23	24	49		101	191	263	2	
320	～	340	32	～	34	100	0	79				3	30	23	57		117	217	303		
320	～	340	32	～	34	110	0	79				7	34	30	66		141	251	345		
320	～	340	32	～	34	120	0	79				10	37	34	72		157	277	383	29	
320	～	340	32	～	34	130	0	79				12	40	38	89		183	313	433		
320	～	340	32	～	34	140	0	79				16	43	47	101		211	351	483		
320	～	340	32	～	34	150	0	79				20	47	50	116		237	387	529	91	
320	～	340	32	～	34	160	0	79			2	21	51	54	123		255	415	573		
340	～	360	34	～	36	10	0	79									5	15	8		
340	～	360	34	～	36	20	0	79						3	4		12	32	34		
340	～	360	34	～	36	30	0	79					3	5	8		21	51	65	-1	
340	～	360	34	～	36	40	0	79					6	7	19		37	77	99		
340	～	360	34	～	36	50	0	79					9	11	23		48	98	134		
340	～	360	34	～	36	60	0	79					14	17	29		65	125	171	0	
340	～	360	34	～	36	70	0	79				1	18	19	34		77	147	206		
340	～	360	34	～	36	80	0	79				3	22	23	46		99	179	250		
340	～	360	34	～	36	90	0	79				5	27	25	53		115	205	290	2	-2
340	～	360	34	～	36	100	0	79				9	33	30	64		141	241	337		
340	～	360	34	～	36	110	0	79				13	37	33	71		159	269	378		9
340	～	360	34	～	36	120	0	79				16	40	37	88		186	306	429	42	
340	～	360	34	～	36	130	0	79			3	18	43	48	101		218	348	487		
340	～	360	34	～	36	140	0	79			5	21	48	50	117		246	386	537		
340	～	360	34	～	36	150	0	79			7	23	52	55	124		266	416	583	105	
360	～	380	36	～	38	10	0	79							1		6	16	11		
360	～	380	36	～	38	20	0	79					1	2	5		13	33	38		
360	～	380	36	～	38	30	0	79					4	5	10		24	54	73	-2	-3
360	～	380	36	～	38	40	0	79					7	9	19		40	80	109		-4
360	～	380	36	～	38	50	0	79					11	12	24		52	102	147		-2
360	～	380	36	～	38	60	0	79				2	16	18	30		71	131	185	-3	
360	～	380	36	～	38	70	0	79				3	20	21	37		86	156	227		
360	～	380	36	～	38	80	0	79				7	24	25	50		111	191	273		
360	～	380	36	～	38	90	0	79				11	31	29	62		138	228	322	11	
360	～	380	36	～	38	100	0	79			1	14	36	32	69		157	257	367		
360	～	380	36	～	38	110	0	79			4	15	40	36	86		186	296	422		
360	～	380	36	～	38	120	0	79			7	18	43	47	100		220	340	482	65	
360	～	380	36	～	38	130	0	79			10	21	48	51	116		251	381	538		
360	～	380	36	～	38	140	0	79			12	23	52	55	125		272	412	586		
380	～	400	38	～	40	10	0	79							1		6	16	12		
380	～	400	38	～	40	20	0	79					1	3	5		14	34	42		6
380	～	400	38	～	40	30	0	79					5	5	11		26	56	80	-4	
380	～	400	38	～	40	40	0	79					9	9	19		42	82	117		
380	～	400	38	～	40	50	0	79				1	13	16	23		58	108	162		
380	～	400	38	～	40	60	0	79				4	17	20	32		78	138	201	-4	
380	～	400	38	～	40	70	0	79				7	22	23	46		103	173	250		
380	～	400	38	～	40	80	0	79			1	10	29	24	55		124	204	299		-4
380	～	400	38	～	40	90	0	79			3	14	34	31	67		154	244	352	14	
380	～	400	38	～	40	100	0	79			6	15	39	34	82		181	281	404		20
380	～	400	38	～	40	110	0	79			10	17	43	41	100		216	326	468		
380	～	400	38	～	40	120	0	79			13	21	47	50	115		251	371	530	90	
380	～	400	38	～	40	130	0	79			1	14	52	55	124		275	405	584		

※ 他減圧表との差については、プラスが増加、マイナスが減少
※ 最大高圧下の時間は、総作業業務時間が600分を超えない範囲で設定(480分+残業120分)
※ CPTDが600を超えない範囲で設定

現行高圧則別表1 一覽

深度 (msw)	時間 (min)	減圧停止時間(min)					減圧時間 (min)	総時間 (min)
		15msw	12msw	9msw	6msw	3msw		
12	30					1	3	33
	60					1	3	63
	90					1	3	93
	120					1	3	123
	150					2	4	154
	180					3	5	185
	210					4	6	216
	240					5	7	247
	270					5	7	277
	300					6	8	308
	330					6	8	338
	360					7	9	369
14	30					1	3	33
	60					1	3	63
	90					1	3	93
	120					3	5	125
	150					5	7	157
	180					6	8	188
	210					8	10	220
	240					10	12	252
	270					10	12	282
	300					10	12	312
	330					12	14	344
16	30					1	3	33
	60					1	3	63
	90					3	5	95
	120					5	7	127
	150					7	9	159
	180					9	11	191
	210					11	13	223
	240					15	17	257
	270					18	20	290
	300					23	25	325
18	30					1	3	33
	60					5	7	67
	90					9	11	101
	120					13	15	135
	150				2	15	19	169
	180				5	20	27	207
	210				8	25	35	245
	240				9	30	41	281
	270				10	35	47	317
	300				17	35	54	354
20	30					1	4	34
	60					8	11	71
	90					16	19	109
	120				7	15	25	145
	150				9	20	32	182
	180				11	30	44	224
	210				15	35	53	263
	240				20	40	63	303
	270				25	45	73	343

22	30			1	4	34
	60			11	14	74
	90		8	15	26	116
	120		12	20	35	155
	150		15	30	48	198
	180		23	40	66	246
	210		25	45	73	283
	240		30	50	83	323
	270		31	60	94	364
24	30			1	4	34
	60			14	17	77
	90		9	20	32	122
	120		18	30	51	171
	150		26	35	64	214
	180	5	30	40	78	258
	210	10	30	50	93	303
	240	14	30	60	107	347
26	30			1	4	34
	60			20	23	83
	90		13	25	41	131
	120		19	35	57	177
	150		33	45	81	231
	180	6	35	50	94	274
	210	15	35	55	108	318
	240	18	35	65	121	361
28	30			2	6	36
	60		10	15	29	89
	90		17	30	51	141
	120	9	25	35	73	193
	150	15	30	45	94	244
	180	16	35	55	110	290
	210	21	40	60	125	335
30	15			2	6	21
	30			5	9	39
	45		3	15	22	67
	60		13	20	37	97
	75		18	30	52	127
	90	4	20	40	68	158
	105	11	25	40	80	185
	120	13	30	45	92	212
	135	15	35	45	99	234
	150	18	35	50	107	257
	165	23	35	55	117	282
	180	20	40	60	124	304
	195	24	40	65	133	328
	210	26	40	75	145	355
32	15			2	6	21
	30			9	13	43
	45		11	15	30	75
	60		18	25	47	107
	75		25	35	64	139
	90	10	25	40	79	169
	105	12	30	45	91	196
	120	15	35	50	104	224
	135	20	40	50	114	249
	150	20	40	60	124	274
	165	22	40	65	131	296
	180	25	40	70	139	319
	195	5	25	40	75	344

34	15				2	6	21
	30				13	17	47
	45			14	20	38	83
	60			21	30	55	115
	75		13	25	35	77	152
	90		15	35	45	99	189
	105	5	15	35	55	114	219
	120	9	15	40	60	128	248
	135	10	20	40	65	139	274
	150	12	25	40	65	146	296
36	165	14	25	40	70	153	318
	180	16	25	40	75	160	340
	15				2	7	22
	30				17	22	52
	45			15	25	45	90
	60		5	20	35	65	125
	75		11	25	50	91	166
	90		18	30	60	113	203
	105		25	35	65	130	235
	120	9	25	40	65	144	264
38	135	14	25	40	70	154	289
	150	16	25	40	75	161	311
	165	18	25	40	80	168	333
	15				2	7	22
	30				21	26	56
	45			20	25	50	95
	60		9	25	35	74	134
	75	5	15	30	50	105	180
	90	12	20	30	60	127	217
	105	14	25	35	65	144	249
40	120	5	15	25	35	70	155
	135	8	20	25	35	70	163
	150	11	20	25	40	70	171
	15				2	7	22
	30				25	30	60
	45			15	35	55	100
	60		12	20	45	82	142
	75	7	20	30	55	117	192
	90	15	20	35	65	140	230
	105	7	15	20	35	70	152
40	120	11	15	25	35	70	161
	135	11	20	25	40	70	171
							306

現行高圧則別表2 一覧

深度 (msw)	時間 (min)	減圧停止時間(min)								減圧時間 (min)	総時間 (min)
		24msw	21msw	18msw	15msw	12msw	9msw	6msw	3msw		
12	10									2	12
	30									2	32
	60									2	62
	90									2	92
	120									2	122
	180								3	5	185
	240								5	7	247
	360								7	9	369
14	10									2	12
	30									2	32
	60									2	62
	90									2	92
	120								4	6	126
	150								6	8	158
	180								7	9	189
	210								9	11	221
16	240								10	12	252
	300								12	14	314
16	10									2	12
	30									2	32
	50									2	52
	70									2	72
	90								3	5	95
	120								6	8	128
	150								9	11	161
	180								12	14	194
18	210								13	15	225
	270								17	19	289
18	10									2	12
	25									2	27
	40									2	42
	55									2	57
	75								2	4	79
	105								11	13	118
	135								16	18	153
	150							4	16	22	172
20	180							7	16	25	205
	240							9	21	32	272
20	10									3	13
	25									3	28
	35									3	38
	50									3	53
	65								9	12	77
	95								16	19	114
	115						7		16	26	141
	135						10		16	29	164
22	165						15		27	45	210
	225						18		34	55	280
22	15									3	18
	30									3	33
	42									3	45
	60								7	10	70
	75								16	19	94
	85						5		16	24	109
	100						12		16	31	131
	120						17		22	42	162
24	150						21		29	53	203
	210						25		39	67	277
24	10									3	13
	25									3	28
	37									3	40
	50								6	9	59
	58								14	17	75
	75						16		14	33	108
	90						18		16	37	127
	108						21		22	46	154
24	145						27		32	62	207
	180						29		41	73	253

26	10					3	13
	20					3	23
	32					3	35
	45				7	10	55
	55				16	19	74
	65			8	16	27	92
	80			18	16	37	117
	100			26	22	51	151
	110			27	25	55	165
	160			29	41	73	233
28	10					4	14
	20					4	24
	28					4	32
	40				6	10	50
	44				11	15	59
	49				16	20	69
	60			11	16	31	91
	70			18	22	44	114
	90			27	22	53	143
	110			27	29	60	170
	140			29	41	74	214
30	10					4	14
	20					4	24
	25					4	29
	35				4	8	43
	39				10	14	53
	44				16	20	64
	50			8	16	28	78
	60			16	16	36	96
	78			27	22	53	131
	85		5	27	22	58	143
32	105		12	27	32	75	180
	130		17	29	48	98	228
	10					4	14
	22					4	26
	30				8	12	42
	35				14	18	53
	40				22	26	66
	46			9	22	35	81
	53			16	22	42	95
	68			27	22	53	121
34	79		7	27	33	71	150
	100		17	27	48	96	196
	120		21	27	55	107	227
	10					4	14
	19					4	23
	27				7	11	38
	31				22	26	57
	36				22	26	62
	41			8	22	34	75
	48			16	22	42	90
36	60			27	22	53	113
	73		10	27	37	78	151
	95		19	27	63	113	208
	115	5	22	32	74	137	252
	5					5	10
	17					5	22
	25				8	13	38
	29				14	19	48
	33				22	27	60
	38			9	22	36	74
36	43			16	22	43	86
	55			27	22	54	109
	67		10	27	34	76	143
	90		22	27	63	117	207
	110	9	22	34	80	150	260

38	5						5	10
	15						5	20
	22						10	32
	26						14	45
	30						22	57
	34					9	22	70
	40					17	22	84
	50					27	22	104
	62					12	27	140
	85					4	22	210
	105					12	22	263
40	5						5	10
	15						5	20
	20						3	8
	24						14	19
	28						22	27
	32					9	22	36
	37					18	22	45
	46					27	22	54
	58					14	27	74
	80					6	22	128
	100					16	22	161
42	13						2	7
	16						4	9
	21						11	16
	26						22	27
	29					9	22	36
	35					14	22	41
	42					27	28	60
	55					15	27	81
	75					8	22	127
	95					16	22	159
45	10						2	7
	14						8	13
	20						14	19
	24						22	27
	30					15	28	48
	37					27	28	60
	50					16	27	82
	70					11	22	133
	90					4	19	187
50	8						2	7
	12						8	13
	16						16	21
	20						28	33
	26					16	28	49
	33					27	28	60
	43					18	27	81
	60					13	23	136
	80					9	19	185
55	6						2	7
	10						7	12
	12						17	22
	14						27	32
	17						36	41
	21					14	36	55
	27					27	36	68
	37					18	27	94
	55					6	28	213
	75					8	18	287
60	5						2	7
	10						16	21
	15						36	41
	24					23	36	64
	33					16	27	90
	50					9	20	220
	70					14	18	304
65	5						5	10
	12						32	37
	21						36	64
	30					2	24	139
	45					6	20	212
	65					4	16	307

70	5								10	15	20
	11								34	39	50
	18							25	36	66	84
	27				4	24	28	35	45	141	168
	40			12	20	24	28	65	95	249	289
	60	8	16	17	20	27	52	95	105	345	405
80	5								16	21	26
	10							8	35	48	58
	15							28	35	68	83
	22				7	24	28	37	51	152	174
	35			18	20	24	30	65	100	262	297
	50	12	16	18	20	28	52	95	105	351	401
90	5								30	35	40
	10							20	35	60	70
	15						14	28	35	82	97
	20				13	24	28	44	51	165	185
	30		6	18	20	24	29	65	100	267	297
	40	12	16	18	20	24	49	90	105	339	379