

潜水潜函共有 空気呼吸 空気減圧表 検討

安全率 21～3m:1.00 加圧速度 8m／min 減圧速度 8m／min 水蒸気圧を考慮しない → 大気圧:10m

帯底圧力(msw)		高圧下 時間(min)	He(%)	N2(%)	空気呼吸 減圧速度8m/min				空気呼吸 減圧速度8m/min				減圧時間	総業務 時間	別表1 差	別表2 差
を超え	以下				24'	21'	18'	15'	12'	9'	6'	3'				
8	10	10	0	79									1	11		
8	10	20	0	79									1	21		
8	10	30	0	79									1	31		
8	10	40	0	79									1	41		
8	10	50	0	79									1	51		
8	10	60	0	79									1	61		
8	10	70	0	79									1	71		
8	10	80	0	79									1	81		
8	10	90	0	79									1	91		
8	10	100	0	79									1	101		
8	10	110	0	79									1	111		
8	10	120	0	79									1	121		
8	10	130	0	79									1	131		
8	10	140	0	79									1	141		
8	10	150	0	79									1	151		
8	10	160	0	79									1	161		
8	10	170	0	79									1	171		
8	10	180	0	79									1	181		
8	10	190	0	79									1	191		
8	10	200	0	79									1	201		
8	10	210	0	79									1	211		
8	10	220	0	79									1	221		
8	10	230	0	79									1	231		
8	10	240	0	79									1	241		
8	10	250	0	79									1	251		
8	10	260	0	79									1	261		
8	10	270	0	79									1	271		
8	10	280	0	79									1	281		
8	10	290	0	79									1	291		
8	10	300	0	79									1	301		
8	10	310	0	79									1	311		
8	10	320	0	79									1	321		
8	10	330	0	79									1	331		
8	10	340	0	79									1	341		
8	10	350	0	79									1	351		
8	10	360	0	79									1	361		
8	10	370	0	79									1	371		
8	10	380	0	79									1	381		
8	10	390	0	79									1	391		
8	10	400	0	79									1	401		
8	10	410	0	79									1	411		
8	10	420	0	79									1	421		
8	10	430	0	79									1	431		
8	10	440	0	79									1	441		
8	10	450	0	79									1	451		
8	10	460	0	79									1	461		
8	10	470	0	79									1	471		
8	10	480	0	79									1	481		
8	10	490	0	79									1	491		
8	10	500	0	79									1	501		
8	10	510	0	79									1	511		
8	10	520	0	79									1	521		
8	10	530	0	79									1	531		
8	10	540	0	79									1	541		
8	10	550	0	79									1	551		
8	10	560	0	79									1	561		
8	10	570	0	79								2	3	573		
8	10	580	0	79								3	4	584		
8	10	590	0	79								5	6	596		
10	12	10	0	79									2	12		0
10	12	20	0	79									2	22		
10	12	30	0	79									2	32	-1	0
10	12	40	0	79									2	42		
10	12	50	0	79									2	52		
10	12	60	0	79									2	62	-1	0
10	12	70	0	79									2	72		
10	12	80	0	79									2	82		
10	12	90	0	79									2	92	-1	0
10	12	100	0	79									2	102		
10	12	110	0	79									2	112		
10	12	120	0	79									2	122	-1	0
10	12	130	0	79									2	132		
10	12	140	0	79									2	142		
10	12	150	0	79									2	152	-2	

安全率 21～3m:1.00 加圧速度 8m／min 減圧速度 8m／min 水蒸気圧を考慮しない → 大気圧:10m

帯底圧力(msw)				高圧下 時間(min)	He(%)	N2(%)	空気呼吸 減圧速度8m/min				空気呼吸 減圧速度8m/min				減圧時間	総業務 時間	別表1 差	別表2 差
を超え		以下					24	21	18	15	12	9	6	3				
10	～	12		160	0	79									2	162		
10	～	12		170	0	79									2	172		
10	～	12		180	0	79									2	182	-3	-3
10	～	12		190	0	79									2	192		
10	～	12		200	0	79									2	202		
10	～	12		210	0	79									2	212	-4	
10	～	12		220	0	79									2	222		
10	～	12		230	0	79									2	232		
10	～	12		240	0	79									2	242	-5	-5
10	～	12		250	0	79									2	252		
10	～	12		260	0	79								1	3	263		
10	～	12		270	0	79								3	5	275	-2	
10	～	12		280	0	79								4	6	286		
10	～	12		290	0	79								5	7	297		
10	～	12		300	0	79								6	8	308	0	
10	～	12		310	0	79								7	9	319		
10	～	12		320	0	79								8	10	330		
10	～	12		330	0	79								10	12	342	4	
10	～	12		340	0	79								12	14	354		
10	～	12		350	0	79								14	16	366		
10	～	12		360	0	79								17	19	379	10	10
10	～	12		370	0	79								21	23	393		
10	～	12		380	0	79								23	25	405		
10	～	12		390	0	79								26	28	418		
10	～	12		400	0	79								29	31	431		
10	～	12		410	0	79								31	33	443		
10	～	12		420	0	79								33	35	455		
10	～	12		430	0	79								35	37	467		
10	～	12		440	0	79								39	41	481		
10	～	12		450	0	79								42	44	494		
10	～	12		460	0	79								46	48	508		
10	～	12		470	0	79								49	51	521		
10	～	12		480	0	79								52	54	534		
10	～	12		490	0	79								54	56	546		
10	～	12		500	0	79								57	59	559		
10	～	12		510	0	79								60	62	572		
10	～	12		520	0	79								62	64	584		
10	～	12		530	0	79								64	66	596		
12	～	14		10	0	79									2	12		0
12	～	14		20	0	79									2	22		
12	～	14		30	0	79									2	32	-1	0
12	～	14		40	0	79									2	42		
12	～	14		50	0	79									2	52		
12	～	14		60	0	79									2	62	-1	0
12	～	14		70	0	79									2	72		
12	～	14		80	0	79									2	82		
12	～	14		90	0	79									2	92	-1	0
12	～	14		100	0	79									2	102		
12	～	14		110	0	79									2	112		
12	～	14		120	0	79									2	122	-3	-4
12	～	14		130	0	79									2	132		
12	～	14		140	0	79									2	142		
12	～	14		150	0	79								1	3	153	-4	-5
12	～	14		160	0	79								3	5	165		
12	～	14		170	0	79								5	7	177		
12	～	14		180	0	79								7	9	189	1	0
12	～	14		190	0	79								10	12	202		
12	～	14		200	0	79								13	15	215		
12	～	14		210	0	79								15	17	227	7	6
12	～	14		220	0	79								18	20	240		
12	～	14		230	0	79								20	22	252		
12	～	14		240	0	79								21	23	263	11	11
12	～	14		250	0	79								23	25	275		
12	～	14		260	0	79								26	28	288		
12	～	14		270	0	79								29	31	301	19	
12	～	14		280	0	79								32	34	314		
12	～	14		290	0	79								36	38	328		
12	～	14		300	0	79								41	43	343	31	29
12	～	14		310	0	79								45	47	357		
12	～	14		320	0	79								49	51	371		
12	～	14		330	0	79								53	55	385	41	
12	～	14		340	0	79								56	58	398		
12	～	14		350	0	79								60	62	412		
12	～	14		360	0	79								65	67	427		
12	～	14		370	0	79								69	71	441		
12	～	14		380	0	79								74	76	456		
12	～	14		390	0	79								78	80	470		

安全率 21～3m:1.00 加圧速度 8m／min 減圧速度 8m／min 水蒸気圧を考慮しない → 大気圧:10m

帯底圧力 (msw)				高圧下 時間(min)	He(%)	N2(%)	空気呼吸 減圧速度8m/min				空気呼吸 減圧速度8m/min				減圧時間	総業務 時間	別表1 差	別表2 差
を 超え			以下				24	21	18	15	12	9	6	3				
12	～		14	400	0	79								83	85	485		
12	～		14	410	0	79								87	89	499		
12	～		14	420	0	79								90	92	512		
12	～		14	430	0	79								94	96	526		
12	～		14	440	0	79								97	99	539		
12	～		14	450	0	79								103	105	555		
12	～		14	460	0	79								111	113	573		
12	～		14	470	0	79								119	121	591		
14	～		16	10	0	79									2	12		0
14	～		16	20	0	79									2	22		
14	～		16	30	0	79									2	32	-1	0
14	～		16	40	0	79									2	42		
14	～		16	50	0	79									2	52		0
14	～		16	60	0	79									2	62	-1	
14	～		16	70	0	79									2	72		0
14	～		16	80	0	79									2	82		
14	～		16	90	0	79									2	92	-3	-3
14	～		16	100	0	79								1	3	103		
14	～		16	110	0	79								3	5	115		
14	～		16	120	0	79								6	8	128	1	0
14	～		16	130	0	79								10	12	142		
14	～		16	140	0	79								12	14	154		
14	～		16	150	0	79								15	17	167	8	6
14	～		16	160	0	79								20	22	182		
14	～		16	170	0	79								23	25	195		
14	～		16	180	0	79								27	29	209	18	15
14	～		16	190	0	79								30	32	222		
14	～		16	200	0	79								32	34	234		
14	～		16	210	0	79								35	37	247	24	22
14	～		16	220	0	79								39	41	261		
14	～		16	230	0	79								43	45	275		
14	～		16	240	0	79								48	50	290	33	
14	～		16	250	0	79								54	56	306		
14	～		16	260	0	79								60	62	322		
14	～		16	270	0	79								65	67	337	47	48
14	～		16	280	0	79								70	72	352		
14	～		16	290	0	79								75	77	367		
14	～		16	300	0	79								80	82	382	57	
14	～		16	310	0	79								87	89	399		
14	～		16	320	0	79							1	91	94	414		
14	～		16	330	0	79						2		96	100	430		
14	～		16	340	0	79						3		101	106	446		
14	～		16	350	0	79						4		106	112	462		
14	～		16	360	0	79						4		110	116	476		
14	～		16	370	0	79						5		114	121	491		
14	～		16	380	0	79						6		120	128	508		
14	～		16	390	0	79						8		130	140	530		
14	～		16	400	0	79						9		139	150	550		
14	～		16	410	0	79						10		148	160	570		
14	～		16	420	0	79						12		156	170	590		
16	～		18	10	0	79									2	12		0
16	～		18	20	0	79									2	22		
16	～		18	30	0	79									2	32	-1	
16	～		18	40	0	79									2	42		0
16	～		18	50	0	79									2	52		
16	～		18	60	0	79									2	62	-5	
16	～		18	70	0	79									2	72		
16	～		18	80	0	79								3	5	85		
16	～		18	90	0	79								7	9	99	-2	
16	～		18	100	0	79								10	12	112		
16	～		18	110	0	79								15	17	127		
16	～		18	120	0	79								18	20	140	5	
16	～		18	130	0	79								22	24	154		
16	～		18	140	0	79								28	30	170		
16	～		18	150	0	79								32	34	184	15	12
16	～		18	160	0	79								36	38	198		
16	～		18	170	0	79								40	42	212		
16	～		18	180	0	79								43	45	225	18	20
16	～		18	190	0	79								46	50	240		
16	～		18	200	0	79						2		51	56	256		
16	～		18	210	0	79						4		57	63	273	28	
16	～		18	220	0	79						6		63	71	291		
16	～		18	230	0	79						9		68	79	309		
16	～		18	240	0	79						11		73	86	326	45	54
16	～		18	250	0	79						13		78	93	343		
16	～		18	260	0	79						14		84	100	360		
16	～		18	270	0	79						16		91	109	379	62	

安全率 21～3m:1.00 加圧速度 8m／min 減圧速度 8m／min 水蒸気圧を考慮しない → 大気圧:10m

帯底圧力 (msw)				高圧下 時間(min)	He(%)	N2(%)	空気呼吸 減圧速度8m/min				空気呼吸 減圧速度8m/min				減圧時間	総業務 時間	別表1 差	別表2 差
を超え			以下				24	21	18	15	12	9	6	3				
16	～		18	280	0	79							17	97	116	396		
16	～		18	290	0	79							19	103	124	414		
16	～		18	300	0	79							20	109	131	431	77	
16	～		18	310	0	79							22	114	138	448		
16	～		18	320	0	79							25	117	144	464		
16	～		18	330	0	79							27	126	155	485		
16	～		18	340	0	79							29	138	169	509		
16	～		18	350	0	79							31	148	181	531		
16	～		18	360	0	79							35	157	194	554		
16	～		18	370	0	79							39	165	206	576		
16	～		18	380	0	79							42	174	218	598		
18	～		20	10	0	79									3	13		0
18	～		20	20	0	79									3	23		
18	～		20	30	0	79									3	33	-1	
18	～		20	40	0	79									3	43		
18	～		20	50	0	79									3	53		0
18	～		20	60	0	79								2	5	65	-6	
18	～		20	70	0	79								7	10	80		
18	～		20	80	0	79								11	14	94		
18	～		20	90	0	79								15	18	108	-1	
18	～		20	100	0	79								21	24	124		
18	～		20	110	0	79								25	28	138		
18	～		20	120	0	79								31	34	154	9	
18	～		20	130	0	79							2	35	40	170		
18	～		20	140	0	79							4	39	46	186		
18	～		20	150	0	79							6	42	51	201	19	
18	～		20	160	0	79							9	44	56	216		
18	～		20	170	0	79							11	50	64	234		
18	～		20	180	0	79							13	55	71	251	27	
18	～		20	190	0	79							16	62	81	271		
18	～		20	200	0	79							19	69	91	291		
18	～		20	210	0	79							22	74	99	309	46	
18	～		20	220	0	79							25	79	107	327		
18	～		20	230	0	79							27	87	117	347		
18	～		20	240	0	79							29	95	127	367	64	
18	～		20	250	0	79							31	102	136	386		
18	～		20	260	0	79							33	109	145	405		
18	～		20	270	0	79							37	114	154	424	81	
18	～		20	280	0	79							40	119	162	442		
18	～		20	290	0	79							43	129	175	465		
18	～		20	300	0	79							46	141	190	490		
18	～		20	310	0	79							51	152	206	516		
18	～		20	320	0	79							55	163	221	541		
18	～		20	330	0	79							60	172	235	565		
18	～		20	340	0	79							64	181	248	588		
20	～		22	10	0	79									3	13		
20	～		22	20	0	79									3	23		
20	～		22	30	0	79									3	33	-1	0
20	～		22	40	0	79									3	43		
20	～		22	50	0	79								3	6	56		
20	～		22	60	0	79								8	11	71	-3	1
20	～		22	70	0	79								13	16	86		
20	～		22	80	0	79								19	22	102		
20	～		22	90	0	79								25	28	118	2	
20	～		22	100	0	79							3	27	33	133		2
20	～		22	110	0	79							6	33	42	152		
20	～		22	120	0	79							8	38	49	169	14	7
20	～		22	130	0	79							12	41	56	186		
20	～		22	140	0	79							15	44	62	202		
20	～		22	150	0	79							18	50	71	221	23	18
20	～		22	160	0	79							20	56	79	239		
20	～		22	170	0	79							25	64	92	262		
20	～		22	180	0	79							29	71	103	283	37	
20	～		22	190	0	79							32	77	112	302		
20	～		22	200	0	79							35	84	122	322		
20	～		22	210	0	79							38	93	134	344	61	67
20	～		22	220	0	79						1	39	102	145	365		
20	～		22	230	0	79						2	42	109	156	386		
20	～		22	240	0	79						2	46	115	166	406	83	
20	～		22	250	0	79						4	49	120	176	426		
20	～		22	260	0	79						6	51	134	194	454		
20	～		22	270	0	79						8	55	148	214	484	120	
20	～		22	280	0	79						10	59	160	232	512		
20	～		22	290	0	79						11	64	171	249	539		
20	～		22	300	0	79						13	68	182	266	566		
20	～		22	310	0	79						14	72	191	280	590		
22	～		24	10	0	79									3	13		0

安全率 21～3m:1.00 加圧速度 8m／min 減圧速度 8m／min 水蒸気圧を考慮しない → 大気圧:10m

帯底圧力 (msw)			高圧下 時間(min)	He(%)	N2(%)	空気呼吸 減圧速度8m/min				空気呼吸 減圧速度8m/min				減圧時間	総業務 時間	別表1 差	別表2 差
を超え		以下				24	21	18	15	12	9	6	3				
22	～	24	20	0	79									3	23		
22	～	24	30	0	79									3	33	-1	
22	～	24	40	0	79								3	6	46		
22	～	24	50	0	79								7	10	60		1
22	～	24	60	0	79								14	17	77	0	
22	～	24	70	0	79								20	23	93		
22	～	24	80	0	79							3	24	30	110		
22	～	24	90	0	79							7	28	38	128	6	1
22	～	24	100	0	79							10	34	47	147		
22	～	24	110	0	79							14	39	56	166		
22	～	24	120	0	79							18	42	63	183	12	
22	～	24	130	0	79							22	47	72	202		
22	～	24	140	0	79							25	54	82	222		
22	～	24	150	0	79						1	29	62	95	245	31	
22	～	24	160	0	79						2	33	70	108	268		
22	～	24	170	0	79						4	35	78	120	290		
22	～	24	180	0	79						6	37	86	132	312	54	59
22	～	24	190	0	79						8	39	97	147	337		
22	～	24	200	0	79						10	41	106	160	360		
22	～	24	210	0	79						11	46	113	173	383	80	
22	～	24	220	0	79						14	49	119	185	405		
22	～	24	230	0	79						17	51	131	202	432		
22	～	24	240	0	79						19	56	146	224	464	117	
22	～	24	250	0	79						21	62	160	246	496		
22	～	24	260	0	79						23	67	172	265	525		
22	～	24	270	0	79						25	71	184	283	553		
22	～	24	280	0	79						26	76	195	300	580		
24	～	26	10	0	79									3	13		0
24	～	26	20	0	79									3	23		0
24	～	26	30	0	79								2	5	35	1	
24	～	26	40	0	79								5	8	48		
24	～	26	50	0	79								13	16	66		
24	～	26	60	0	79							2	18	23	83	0	
24	～	26	70	0	79							5	23	31	101		
24	～	26	80	0	79							10	26	39	119		2
24	～	26	90	0	79							13	35	51	141	10	
24	～	26	100	0	79							18	39	60	160		9
24	～	26	110	0	79						1	22	43	69	179		14
24	～	26	120	0	79						3	24	50	80	200	23	
24	～	26	130	0	79						5	27	57	92	222		
24	～	26	140	0	79						7	32	67	109	249		
24	～	26	150	0	79						10	35	75	123	273	42	
24	～	26	160	0	79						13	37	83	136	296		63
24	～	26	170	0	79						15	39	96	153	323		
24	～	26	180	0	79						17	43	105	168	348	74	
24	～	26	190	0	79						20	47	113	183	373		
24	～	26	200	0	79						24	49	121	197	397		
24	～	26	210	0	79						27	53	135	218	428	110	
24	～	26	220	0	79						30	59	152	244	464		
24	～	26	230	0	79						32	65	166	266	496		
24	～	26	240	0	79						34	71	180	288	528	167	
24	～	26	250	0	79						36	76	192	307	557		
24	～	26	260	0	79						38	80	204	325	585		
26	～	28	10	0	79									4	14		0
26	～	28	20	0	79									4	24		0
26	～	28	30	0	79								4	8	38	2	
26	～	28	40	0	79								9	13	53		3
26	～	28	50	0	79							3	15	22	72		
26	～	28	60	0	79							6	21	31	91	2	0
26	～	28	70	0	79							11	26	41	111		-3
26	～	28	80	0	79							16	32	52	132		
26	～	28	90	0	79						2	19	39	64	154	13	11
26	～	28	100	0	79						5	22	43	74	174		
26	～	28	110	0	79						8	24	51	87	197		27
26	～	28	120	0	79						10	29	59	102	222	29	
26	～	28	130	0	79						13	33	70	120	250		
26	～	28	140	0	79						17	36	79	136	276		62
26	～	28	150	0	79						20	38	90	152	302	58	
26	～	28	160	0	79						22	41	102	169	329		
26	～	28	170	0	79						26	46	111	187	357		
26	～	28	180	0	79					1	28	50	119	202	382	92	
26	～	28	190	0	79					3	31	53	134	225	415		
26	～	28	200	0	79					5	32	61	152	254	454		
26	～	28	210	0	79					6	35	67	168	280	490	155	
26	～	28	220	0	79					8	36	73	184	305	525		
26	～	28	230	0	79					9	37	79	197	326	556		
26	～	28	240	0	79					11	40	83	210	348	588		

安全率 21～3m:1.00 加圧速度 8m／min 減圧速度 8m／min 水蒸気圧を考慮しない → 大気圧:10m

帯底圧力 (msw)		高压下 時間(min)	He(%)	N2(%)	空気呼吸 減圧速度8m/min				空気呼吸 減圧速度8m/min				減圧時間	総業務 時間	別表1 差	別表2 差
を超え	以下				24	21	18	15	12	9	6	3				
28	～	30	0	79									4	14		0
28	～	30	0	79									4	24		0
28	～	30	0	79								6	10	40	1	
28	～	30	0	79							2	12	18	58		
28	～	30	0	79							5	18	27	77		-1
28	～	30	0	79							11	23	38	98	1	2
28	～	30	0	79						1	16	30	51	121		
28	～	30	0	79						4	19	38	65	145		
28	～	30	0	79						8	21	43	76	166	8	
28	～	30	0	79						11	24	50	89	189		
28	～	30	0	79						13	30	59	106	216		
28	～	30	0	79						18	34	70	126	246	34	
28	～	30	0	79					1	21	37	81	144	274		46
28	～	30	0	79					3	22	40	94	163	303		
28	～	30	0	79					4	25	44	106	183	333	76	
28	～	30	0	79					7	28	48	116	203	363		
28	～	30	0	79					9	31	52	126	222	392		
28	～	30	0	79					11	33	60	147	255	435	131	
28	～	30	0	79					13	35	67	165	284	474		
28	～	30	0	79					15	36	74	182	311	511		
28	～	30	0	79					17	39	79	197	336	546	191	
28	～	30	0	79					20	42	84	211	361	581		
30	～	32	0	79									4	14		0
30	～	32	0	79								2	6	26		
30	～	32	0	79								8	12	42	-1	0
30	～	32	0	79							4	14	22	62		-4
30	～	32	0	79							8	21	33	83		
30	～	32	0	79						2	14	26	46	106	-1	
30	～	32	0	79						5	17	35	61	131		
30	～	32	0	79						9	20	41	74	154		
30	～	32	0	79						13	24	48	89	179	10	
30	～	32	0	79						16	29	57	106	206		10
30	～	32	0	79					3	19	34	70	130	240		
30	～	32	0	79					6	20	37	81	148	268	44	41
30	～	32	0	79					7	23	41	95	170	300		
30	～	32	0	79					10	26	45	108	193	333		
30	～	32	0	79					13	29	50	118	214	364	90	
30	～	32	0	79					16	32	55	134	241	401		
30	～	32	0	79					18	34	64	155	275	445		
30	～	32	0	79					20	37	71	174	306	486	167	
30	～	32	0	79					23	38	78	191	334	524		
30	～	32	0	79				1	26	41	83	208	363	563		
32	～	34	0	79									4	14		0
32	～	34	0	79								3	7	27		
32	～	34	0	79							2	9	15	45	-2	
32	～	34	0	79							6	17	27	67		
32	～	34	0	79						2	11	23	40	90		
32	～	34	0	79						5	16	29	54	114	-1	1
32	～	34	0	79						9	19	38	70	140		
32	～	34	0	79						14	23	44	85	165		
32	～	34	0	79					2	16	27	54	103	193	4	
32	～	34	0	79					6	18	33	67	128	228		
32	～	34	0	79					9	20	37	80	150	260		
32	～	34	0	79					11	23	41	94	173	293	45	
32	～	34	0	79					14	27	45	109	199	329		
32	～	34	0	79					18	30	50	120	222	362		
32	～	34	0	79				1	20	33	57	138	253	403	107	
32	～	34	0	79				2	22	36	66	161	291	451		
32	～	34	0	79				4	23	38	75	181	325	495		
32	～	34	0	79				6	26	40	81	200	357	537	197	
32	～	34	0	79				8	29	44	88	215	388	578		
34	～	36	0	79									5	15		
34	～	36	0	79								5	10	30		
34	～	36	0	79							4	9	18	48	-4	
34	～	36	0	79						1	8	17	31	71		
34	～	36	0	79						4	13	25	47	97		
34	～	36	0	79						8	16	34	63	123	-2	
34	～	36	0	79					1	13	21	41	81	151		
34	～	36	0	79					4	15	25	50	99	179		
34	～	36	0	79					8	16	32	62	123	213	10	6
34	～	36	0	79					11	20	36	77	149	249		
34	～	36	0	79					14	23	40	91	173	283		23
34	～	36	0	79				2	16	26	45	108	202	322	58	
34	～	36	0	79				4	18	31	50	120	228	358		
34	～	36	0	79				6	20	34	58	140	263	403		
34	～	36	0	79				7	22	37	68	164	303	453	142	
34	～	36	0	79				10	25	37	77	186	340	500		

安全率 21～3m:1.00 加圧速度 8m／min 減圧速度 8m／min 水蒸気圧を考慮しない → 大気圧:10m

帯底圧力(msw)				高圧下 時間(min)	He(%)	N2(%)	空気呼吸 減圧速度8m/min				空気呼吸 減圧速度8m/min				減圧時間	総業務 時間	別表1 差	別表2 差
を超え			以下				24	21	18	15	12	9	6	3				
34	～		36	170	0	79				12	28	42	82	206	375	545		
34	～		36	180	0	79				15	30	45	92	220	407	587		
36	～		38	10	0	79									5	15		
36	～		38	20	0	79								6	11	31		
36	～		38	30	0	79							6	11	22	52	-4	-5
36	～		38	40	0	79						3	9	19	36	76		-8
36	～		38	50	0	79						7	14	27	53	103		-1
36	～		38	60	0	79					2	10	18	38	73	133	-1	
36	～		38	70	0	79					5	14	23	44	91	161		
36	～		38	80	0	79					8	16	29	55	113	193		
36	～		38	90	0	79					12	19	35	71	142	232	15	
36	～		38	100	0	79				1	15	22	39	86	168	268		
36	～		38	110	0	79				5	16	25	44	105	200	310		
36	～		38	120	0	79				7	19	30	50	118	229	349	74	
36	～		38	130	0	79				9	21	34	58	138	265	395		
36	～		38	140	0	79				11	23	37	68	164	308	448		
36	～		38	150	0	79				15	25	38	78	187	348	498	177	
36	～		38	160	0	79				18	28	43	84	208	386	546		
36	～		38	170	0	79			1	19	31	47	95	223	421	591		
38	～		40	10	0	79									5	15		
38	～		40	20	0	79							1	7	13	33		5
38	～		40	30	0	79							7	14	26	56	-4	
38	～		40	40	0	79						5	10	22	42	82		
38	～		40	50	0	79					2	8	15	31	61	111		
38	～		40	60	0	79					4	12	21	40	82	142	0	
38	～		40	70	0	79					8	15	25	50	103	173		
38	～		40	80	0	79				1	12	17	32	64	131	211		3
38	～		40	90	0	79				3	14	22	37	80	161	251	21	
38	～		40	100	0	79				7	15	24	42	99	192	292		31
38	～		40	110	0	79				10	18	29	49	115	226	336		
38	～		40	120	0	79				12	21	33	56	132	259	379	98	
38	～		40	130	0	79			1	14	23	36	68	161	308	438		
38	～		40	140	0	79			3	16	26	38	78	187	353	493		
38	～		40	150	0	79			4	19	29	43	85	209	394	544		
38	～		40	160	0	79			5	20	32	48	96	225	431	591		

※ 他減圧表との差については、プラスが増加、マイナスが減少
※ 最大高圧下の時間は、総作業業務時間が600分を超えない範囲で設定(480分+残業120分)