

潜水潜函共有 空気呼吸 空気減圧表 検討

安全率 21～3m:1.00 加圧速度 8m／min 減圧速度 8m／min 水蒸気圧を考慮する → 大気圧:9.433m

帯底圧力(msw)		高圧下 時間(min)	He(%)	N2(%)	空気呼吸 減圧速度8m/min				空気呼吸 減圧速度8m/min				減圧時間	総業務 時間	別表1 差	別表2 差
を超え	以下				24'	21'	18'	15'	12'	9'	6'	3'				
8	10	10	0	79									1	11		
8	10	20	0	79									1	21		
8	10	30	0	79									1	31		
8	10	40	0	79									1	41		
8	10	50	0	79									1	51		
8	10	60	0	79									1	61		
8	10	70	0	79									1	71		
8	10	80	0	79									1	81		
8	10	90	0	79									1	91		
8	10	100	0	79									1	101		
8	10	110	0	79									1	111		
8	10	120	0	79									1	121		
8	10	130	0	79									1	131		
8	10	140	0	79									1	141		
8	10	150	0	79									1	151		
8	10	160	0	79									1	161		
8	10	170	0	79									1	171		
8	10	180	0	79									1	181		
8	10	190	0	79									1	191		
8	10	200	0	79									1	201		
8	10	210	0	79									1	211		
8	10	220	0	79									1	221		
8	10	230	0	79									1	231		
8	10	240	0	79									1	241		
8	10	250	0	79									1	251		
8	10	260	0	79									1	261		
8	10	270	0	79									1	271		
8	10	280	0	79									1	281		
8	10	290	0	79									1	291		
8	10	300	0	79									1	301		
8	10	310	0	79									1	311		
8	10	320	0	79									1	321		
8	10	330	0	79									1	331		
8	10	340	0	79									1	341		
8	10	350	0	79									1	351		
8	10	360	0	79									1	361		
8	10	370	0	79									1	371		
8	10	380	0	79									1	381		
8	10	390	0	79									1	391		
8	10	400	0	79									1	401		
8	10	410	0	79									1	411		
8	10	420	0	79									1	421		
8	10	430	0	79									1	431		
8	10	440	0	79									1	441		
8	10	450	0	79									1	451		
8	10	460	0	79									1	461		
8	10	470	0	79									1	471		
8	10	480	0	79									1	481		
8	10	490	0	79									1	491		
8	10	500	0	79									1	501		
8	10	510	0	79								1	2	512		
8	10	520	0	79								3	4	524		
8	10	530	0	79								4	5	535		
8	10	540	0	79								5	6	546		
8	10	550	0	79								7	8	558		
8	10	560	0	79								9	10	570		
8	10	570	0	79								11	12	582		
8	10	580	0	79								13	14	594		
10	12	10	0	79									2	12		0
10	12	20	0	79									2	22		
10	12	30	0	79									2	32	-1	0
10	12	40	0	79									2	42		
10	12	50	0	79									2	52		
10	12	60	0	79									2	62	-1	0
10	12	70	0	79									2	72		
10	12	80	0	79									2	82		
10	12	90	0	79									2	92	-1	0
10	12	100	0	79									2	102		
10	12	110	0	79									2	112		
10	12	120	0	79									2	122	-1	0
10	12	130	0	79									2	132		
10	12	140	0	79									2	142		
10	12	150	0	79									2	152	-2	
10	12	160	0	79									2	162		

安全率 21～3m:1.00 加圧速度 8m／min 減圧速度 8m／min 水蒸気圧を考慮する → 大気圧:9.433m

帯底圧力(msw)				高圧下 時間(min)	He(%)	N2(%)	空気呼吸 減圧速度8m/min				空気呼吸 減圧速度8m/min				減圧時間	総業務 時間	別表1 差	別表2 差
を超え			以下				24	21	18	15	12	9	6	3				
10	～		12	170	0	79									2	172		
10	～		12	180	0	79									2	182	-3	-3
10	～		12	190	0	79									2	192		
10	～		12	200	0	79									2	202		
10	～		12	210	0	79									2	212	-4	
10	～		12	220	0	79									2	222		
10	～		12	230	0	79									2	232		
10	～		12	240	0	79								2	4	244	-3	-3
10	～		12	250	0	79								3	5	255		
10	～		12	260	0	79								5	7	267		
10	～		12	270	0	79								6	8	278	1	
10	～		12	280	0	79								8	10	290		
10	～		12	290	0	79								9	11	301		
10	～		12	300	0	79								10	12	312	4	
10	～		12	310	0	79								11	13	323		
10	～		12	320	0	79								13	15	335		
10	～		12	330	0	79								15	17	347	9	
10	～		12	340	0	79								18	20	360		
10	～		12	350	0	79								21	23	373		
10	～		12	360	0	79								25	27	387	18	18
10	～		12	370	0	79								28	30	400		
10	～		12	380	0	79								31	33	413		
10	～		12	390	0	79								33	35	425		
10	～		12	400	0	79								36	38	438		
10	～		12	410	0	79								38	40	450		
10	～		12	420	0	79								41	43	463		
10	～		12	430	0	79								45	47	477		
10	～		12	440	0	79								48	50	490		
10	～		12	450	0	79								52	54	504		
10	～		12	460	0	79								55	57	517		
10	～		12	470	0	79								58	60	530		
10	～		12	480	0	79								61	63	543		
10	～		12	490	0	79								64	66	556		
10	～		12	500	0	79								67	69	569		
10	～		12	510	0	79								69	71	581		
10	～		12	520	0	79								72	74	594		
12	～		14	10	0	79									2	12		0
12	～		14	20	0	79									2	22		
12	～		14	30	0	79									2	32	-1	0
12	～		14	40	0	79									2	42		
12	～		14	50	0	79									2	52		
12	～		14	60	0	79									2	62	-1	0
12	～		14	70	0	79									2	72		
12	～		14	80	0	79									2	82		
12	～		14	90	0	79									2	92	-1	0
12	～		14	100	0	79									2	102		
12	～		14	110	0	79									2	112		
12	～		14	120	0	79									2	122	-3	-4
12	～		14	130	0	79									2	132		
12	～		14	140	0	79								1	3	143		
12	～		14	150	0	79								4	6	156	-1	-2
12	～		14	160	0	79								6	8	168		
12	～		14	170	0	79								7	9	179		
12	～		14	180	0	79								10	12	192	4	3
12	～		14	190	0	79								14	16	206		
12	～		14	200	0	79								16	18	218		
12	～		14	210	0	79								19	21	231	11	10
12	～		14	220	0	79								21	23	243		
12	～		14	230	0	79								23	25	255		
12	～		14	240	0	79								25	27	267	15	15
12	～		14	250	0	79								27	29	279		
12	～		14	260	0	79								31	33	293		
12	～		14	270	0	79								34	36	306	24	
12	～		14	280	0	79								39	41	321		
12	～		14	290	0	79								44	46	336		
12	～		14	300	0	79								48	50	350	38	36
12	～		14	310	0	79								53	55	365		
12	～		14	320	0	79								56	58	378		
12	～		14	330	0	79								60	62	392	48	
12	～		14	340	0	79								64	66	406		
12	～		14	350	0	79								69	71	421		
12	～		14	360	0	79								74	76	436		
12	～		14	370	0	79								79	81	451		
12	～		14	380	0	79								84	86	466		
12	～		14	390	0	79								88	90	480		
12	～		14	400	0	79								92	94	494		
12	～		14	410	0	79								96	98	508		

安全率 21～3m:1.00 加圧速度 8m／min 減圧速度 8m／min 水蒸気圧を考慮する → 大気圧:9.433m

帯底圧力(msw)				高压下 時間(min)	He(%)	N2(%)	空気呼吸 減圧速度8m/min				空気呼吸 減圧速度8m/min				減圧時間	総業務 時間	別表1 差	別表2 差
を超え			以下				24	21	18	15	12	9	6	3				
12	～		14	420	0	79								100	102	522		
12	～		14	430	0	79								103	105	535		
12	～		14	440	0	79								112	114	554		
12	～		14	450	0	79								121	123	573		
12	～		14	460	0	79								129	131	591		
14	～		16	10	0	79									2	12		0
14	～		16	20	0	79									2	22		
14	～		16	30	0	79									2	32	-1	0
14	～		16	40	0	79									2	42		
14	～		16	50	0	79									2	52		0
14	～		16	60	0	79									2	62	-1	
14	～		16	70	0	79									2	72		0
14	～		16	80	0	79									2	82		
14	～		16	90	0	79									2	92	-3	-3
14	～		16	100	0	79								3	5	105		
14	～		16	110	0	79								5	7	117		
14	～		16	120	0	79								9	11	131	4	3
14	～		16	130	0	79								12	14	144		
14	～		16	140	0	79								15	17	157		
14	～		16	150	0	79								19	21	171	12	10
14	～		16	160	0	79								23	25	185		
14	～		16	170	0	79								27	29	199		
14	～		16	180	0	79								30	32	212	21	18
14	～		16	190	0	79								33	35	225		
14	～		16	200	0	79								36	38	238		
14	～		16	210	0	79								40	42	252	29	27
14	～		16	220	0	79								44	46	266		
14	～		16	230	0	79								49	51	281		
14	～		16	240	0	79								55	57	297	40	
14	～		16	250	0	79								62	64	314		
14	～		16	260	0	79								67	69	329		
14	～		16	270	0	79								73	75	345	55	56
14	～		16	280	0	79								78	80	360		
14	～		16	290	0	79							1	81	84	374		
14	～		16	300	0	79						2	87	91	391	66		
14	～		16	310	0	79						3	93	98	408			
14	～		16	320	0	79						4	99	105	425			
14	～		16	330	0	79						5	104	111	441			
14	～		16	340	0	79						6	109	117	457			
14	～		16	350	0	79						7	113	122	472			
14	～		16	360	0	79						7	118	127	487			
14	～		16	370	0	79						9	126	137	507			
14	～		16	380	0	79						10	136	148	528			
14	～		16	390	0	79						12	145	159	549			
14	～		16	400	0	79						13	155	170	570			
14	～		16	410	0	79						15	163	180	590			
16	～		18	10	0	79									2	12		0
16	～		18	20	0	79									2	22		
16	～		18	30	0	79									2	32	-1	
16	～		18	40	0	79									2	42		0
16	～		18	50	0	79									2	52		
16	～		18	60	0	79									2	62	-5	
16	～		18	70	0	79								1	3	73		
16	～		18	80	0	79								5	7	87		
16	～		18	90	0	79								8	10	100	-1	
16	～		18	100	0	79								12	14	114		
16	～		18	110	0	79								17	19	129		
16	～		18	120	0	79								21	23	143	8	
16	～		18	130	0	79								26	28	158		
16	～		18	140	0	79								31	33	173		
16	～		18	150	0	79								36	38	188	19	16
16	～		18	160	0	79								40	42	202		
16	～		18	170	0	79								44	46	216		
16	～		18	180	0	79						2	46	50	230	23	25	
16	～		18	190	0	79						4	50	56	246			
16	～		18	200	0	79						5	56	63	263			
16	～		18	210	0	79						6	63	71	281	36		
16	～		18	220	0	79						9	69	80	300			
16	～		18	230	0	79						12	74	88	318			
16	～		18	240	0	79						14	78	94	334	53	62	
16	～		18	250	0	79						16	84	102	352			
16	～		18	260	0	79						17	92	111	371			
16	～		18	270	0	79						19	98	119	389	72		
16	～		18	280	0	79						20	105	127	407			
16	～		18	290	0	79						22	111	135	425			
16	～		18	300	0	79						24	116	142	442	88		
16	～		18	310	0	79						26	121	149	459			

安全率 21～3m:1.00 加圧速度 8m／min 減圧速度 8m／min 水蒸気圧を考慮する → 大気圧:9.433m

帯底圧力 (msw)				高圧下 時間(min)	He(%)	N2(%)	空気呼吸 減圧速度8m/min				空気呼吸 減圧速度8m/min				減圧時間	総業務 時間	別表1 差	別表2 差
を超え			以下				24	21	18	15	12	9	6	3				
16	～		18	320	0	79							29	130	161	481		
16	～		18	330	0	79							31	142	175	505		
16	～		18	340	0	79							33	153	188	528		
16	～		18	350	0	79							37	163	202	552		
16	～		18	360	0	79							41	171	214	574		
16	～		18	370	0	79							45	180	227	597		
18	～		20	10	0	79									3	13		0
18	～		20	20	0	79									3	23		
18	～		20	30	0	79									3	33	-1	
18	～		20	40	0	79									3	43		
18	～		20	50	0	79									3	53		0
18	～		20	60	0	79								3	6	66	-5	
18	～		20	70	0	79								8	11	81		
18	～		20	80	0	79								12	15	95		
18	～		20	90	0	79								18	21	111	2	
18	～		20	100	0	79								23	26	126		
18	～		20	110	0	79								28	31	141		
18	～		20	120	0	79							1	33	37	157	12	
18	～		20	130	0	79							3	38	44	174		
18	～		20	140	0	79							6	41	50	190		
18	～		20	150	0	79							8	44	55	205	23	
18	～		20	160	0	79							11	48	62	222		
18	～		20	170	0	79							13	53	69	239		
18	～		20	180	0	79							15	61	79	259	35	
18	～		20	190	0	79							19	68	90	280		
18	～		20	200	0	79							22	74	99	299		
18	～		20	210	0	79							25	80	108	318	55	
18	～		20	220	0	79							28	86	117	337		
18	～		20	230	0	79							30	95	128	358		
18	～		20	240	0	79							32	103	138	378	75	
18	～		20	250	0	79							34	110	147	397		
18	～		20	260	0	79							37	116	156	416		
18	～		20	270	0	79							41	121	165	435	92	
18	～		20	280	0	79							44	131	178	458		
18	～		20	290	0	79							47	144	194	484		
18	～		20	300	0	79							52	156	211	511		
18	～		20	310	0	79							57	167	227	537		
18	～		20	320	0	79							62	176	241	561		
18	～		20	330	0	79							66	186	255	585		
20	～		22	10	0	79									3	13		
20	～		22	20	0	79									3	23		
20	～		22	30	0	79									3	33	-1	0
20	～		22	40	0	79								1	4	44		
20	～		22	50	0	79								4	7	57		
20	～		22	60	0	79								9	12	72	-2	2
20	～		22	70	0	79								15	18	88		
20	～		22	80	0	79								21	24	104		
20	～		22	90	0	79							2	25	30	120	4	
20	～		22	100	0	79							5	29	37	137		6
20	～		22	110	0	79							7	36	46	156		
20	～		22	120	0	79							10	40	53	173	18	11
20	～		22	130	0	79							14	43	60	190		
20	～		22	140	0	79							17	48	68	208		
20	～		22	150	0	79							20	54	77	227	29	24
20	～		22	160	0	79							23	62	88	248		
20	～		22	170	0	79							28	69	100	270		
20	～		22	180	0	79							32	76	111	291	45	
20	～		22	190	0	79							35	83	121	311		
20	～		22	200	0	79							38	92	133	333		
20	～		22	210	0	79					1		39	101	144	354	71	77
20	～		22	220	0	79					2		41	110	156	376		
20	～		22	230	0	79					3		45	116	167	397		
20	～		22	240	0	79					5		48	122	178	418	95	
20	～		22	250	0	79					7		51	135	196	446		
20	～		22	260	0	79					9		54	150	216	476		
20	～		22	270	0	79					11		59	163	236	506	142	
20	～		22	280	0	79					12		64	175	254	534		
20	～		22	290	0	79					14		68	186	271	561		
20	～		22	300	0	79					15		72	196	286	586		
22	～		24	10	0	79									3	13		0
22	～		24	20	0	79									3	23		
22	～		24	30	0	79									3	33	-1	
22	～		24	40	0	79								4	7	47		
22	～		24	50	0	79								9	12	62		3
22	～		24	60	0	79								15	18	78	1	
22	～		24	70	0	79							1	22	26	96		
22	～		24	80	0	79							5	25	33	113		

安全率 21～3m:1.00 加圧速度 8m／min 減圧速度 8m／min 水蒸気圧を考慮する → 大気圧:9.433m

帯底圧力 (msw)				高压下 時間(min)	He(%)	N2(%)	空気呼吸 減圧速度8m/min				空気呼吸 減圧速度8m/min				減圧時間	総業務 時間	別表1 差	別表2 差
を超え			以下				24	21	18	15	12	9	6	3				
22	～		24	90	0	79							9	30	42	132	10	5
22	～		24	100	0	79							12	36	51	151		
22	～		24	110	0	79							16	41	60	170		
22	～		24	120	0	79							20	44	67	187	16	
22	～		24	130	0	79							24	51	78	208		
22	～		24	140	0	79						1	26	58	88	228		
22	～		24	150	0	79						2	31	67	103	253	39	
22	～		24	160	0	79						4	34	76	117	277		
22	～		24	170	0	79						6	37	83	129	299		
22	～		24	180	0	79						8	39	94	144	324	66	71
22	～		24	190	0	79						10	41	104	158	348		
22	～		24	200	0	79						11	45	113	172	372		
22	～		24	210	0	79						14	48	120	185	395	92	
22	～		24	220	0	79						17	51	129	200	420		
22	～		24	230	0	79						20	54	147	224	454		
22	～		24	240	0	79						22	61	161	247	487	140	
22	～		24	250	0	79						24	66	175	268	518		
22	～		24	260	0	79						26	71	187	287	547		
22	～		24	270	0	79						28	75	199	305	575		
24	～		26	10	0	79									3	13		0
24	～		26	20	0	79									3	23		0
24	～		26	30	0	79								2	5	35	1	
24	～		26	40	0	79								6	9	49		
24	～		26	50	0	79							1	13	17	67		
24	～		26	60	0	79							3	19	25	85	2	
24	～		26	70	0	79							7	24	34	104		
24	～		26	80	0	79							11	29	43	123		6
24	～		26	90	0	79							15	37	55	145	14	
24	～		26	100	0	79							20	42	65	165		14
24	～		26	110	0	79						2	23	45	73	183		18
24	～		26	120	0	79						4	25	54	86	206	29	
24	～		26	130	0	79						6	30	62	101	231		
24	～		26	140	0	79						9	33	72	117	257		
24	～		26	150	0	79						12	36	81	132	282	51	
24	～		26	160	0	79						15	38	92	148	308		75
24	～		26	170	0	79						17	41	103	164	334		
24	～		26	180	0	79						19	46	112	180	360	86	
24	～		26	190	0	79						23	49	120	195	385		
24	～		26	200	0	79						26	52	132	213	413		
24	～		26	210	0	79						29	58	150	240	450	132	
24	～		26	220	0	79						32	64	166	265	485		
24	～		26	230	0	79						35	70	181	289	519		
24	～		26	240	0	79						37	75	194	309	549	188	
24	～		26	250	0	79					1	37	80	207	328	578		
26	～		28	10	0	79									4	14		0
26	～		28	20	0	79									4	24		0
26	～		28	30	0	79								5	9	39	3	
26	～		28	40	0	79								10	14	54		4
26	～		28	50	0	79							3	17	24	74		
26	～		28	60	0	79							7	22	33	93	4	2
26	～		28	70	0	79							12	27	43	113		-1
26	～		28	80	0	79							17	35	56	136		
26	～		28	90	0	79						3	20	41	68	158	17	15
26	～		28	100	0	79						6	23	45	78	178		
26	～		28	110	0	79						9	25	55	93	203		33
26	～		28	120	0	79						11	31	65	111	231	38	
26	～		28	130	0	79						15	35	75	129	259		
26	～		28	140	0	79						19	37	85	145	285		71
26	～		28	150	0	79						21	41	97	163	313	69	
26	～		28	160	0	79						24	44	109	181	341		
26	～		28	170	0	79					1	27	48	119	199	369		
26	～		28	180	0	79					3	30	52	129	218	398	108	
26	～		28	190	0	79					5	32	58	150	249	439		
26	～		28	200	0	79					7	33	66	167	277	477		
26	～		28	210	0	79					8	36	72	183	303	513	178	
26	～		28	220	0	79					9	37	78	198	326	546		
26	～		28	230	0	79					11	39	83	212	349	579		
28	～		30	10	0	79									4	14		0
28	～		30	20	0	79								1	5	25		1
28	～		30	30	0	79								7	11	41	2	
28	～		30	40	0	79							3	13	20	60		
28	～		30	50	0	79							6	19	29	79		1
28	～		30	60	0	79							12	25	41	101	4	5
28	～		30	70	0	79						2	16	33	55	125		
28	～		30	80	0	79						5	19	40	68	148		
28	～		30	90	0	79						9	22	45	80	170	12	
28	～		30	100	0	79						12	26	54	96	196		

安全率 21～3m:1.00 加圧速度 8m／min 減圧速度 8m／min 水蒸気圧を考慮する → 大気圧:9.433m

帯底圧力 (msw)				高压下 時間(min)	He(%)	N2(%)	空気呼吸 減圧速度8m/min				空気呼吸 減圧速度8m/min				減圧時間	総業務 時間	別表1 差	別表2 差
を超え			以下				24	21	18	15	12	9	6	3				
28	～		30	110	0	79						15	32	64	115	225		
28	～		30	120	0	79						20	35	76	135	255	43	
28	～		30	130	0	79					2	22	39	87	154	284		56
28	～		30	140	0	79					4	23	42	102	175	315		
28	～		30	150	0	79					5	27	46	113	195	345	88	
28	～		30	160	0	79					8	29	51	123	215	375		
28	～		30	170	0	79					11	32	56	142	245	415		
28	～		30	180	0	79					13	34	64	163	278	458	154	
28	～		30	190	0	79					15	36	72	180	307	497		
28	～		30	200	0	79					16	38	78	197	333	533		
28	～		30	210	0	79					20	40	83	212	359	569	214	
30	～		32	10	0	79									4	14		0
30	～		32	20	0	79								2	6	26		
30	～		32	30	0	79							1	8	13	43	0	1
30	～		32	40	0	79							5	15	24	64		-2
30	～		32	50	0	79						1	9	22	36	86		
30	～		32	60	0	79						3	14	28	49	109	2	
30	～		32	70	0	79						6	18	37	65	135		
30	～		32	80	0	79						10	22	43	79	159		
30	～		32	90	0	79						14	25	52	95	185	16	
30	～		32	100	0	79					1	17	31	62	115	215		19
30	～		32	110	0	79					4	20	35	76	139	249		
30	～		32	120	0	79					7	21	39	87	158	278	54	51
30	～		32	130	0	79					9	23	42	104	182	312		
30	～		32	140	0	79					11	27	48	115	205	345		
30	～		32	150	0	79					15	30	52	127	228	378	104	
30	～		32	160	0	79					17	33	60	149	263	423		
30	～		32	170	0	79					20	35	68	171	298	468		
30	～		32	180	0	79					22	38	76	189	329	509	190	
30	～		32	190	0	79					26	39	82	207	358	548		
30	～		32	200	0	79				2	28	43	89	222	388	588		
32	～		34	10	0	79									4	14		0
32	～		34	20	0	79								4	8	28		
32	～		34	30	0	79							3	9	16	46	-1	
32	～		34	40	0	79							7	17	28	68		
32	～		34	50	0	79						3	11	24	42	92		
32	～		34	60	0	79						6	16	32	58	118	3	5
32	～		34	70	0	79						10	20	41	75	145		
32	～		34	80	0	79					1	14	24	47	90	170		
32	～		34	90	0	79					3	17	29	58	111	201	12	
32	～		34	100	0	79					7	19	34	73	137	237		
32	～		34	110	0	79					10	21	39	85	159	269		
32	～		34	120	0	79					12	24	42	103	185	305	57	
32	～		34	130	0	79					16	28	48	116	212	342		
32	～		34	140	0	79				1	19	31	53	129	237	377		
32	～		34	150	0	79				2	21	34	62	154	277	427	131	
32	～		34	160	0	79				3	23	37	71	176	314	474		
32	～		34	170	0	79				5	25	38	80	196	348	518		
32	～		34	180	0	79				8	27	42	85	215	381	561	221	
34	～		36	10	0	79									5	15		
34	～		36	20	0	79								5	10	30		
34	～		36	30	0	79							4	11	20	50	-2	
34	～		36	40	0	79						2	8	18	33	73		
34	～		36	50	0	79						5	14	26	50	100		
34	～		36	60	0	79						9	17	37	68	128	3	
34	～		36	70	0	79					2	13	22	44	86	156		
34	～		36	80	0	79					5	16	26	54	106	186		
34	～		36	90	0	79					9	17	33	69	133	223	20	16
34	～		36	100	0	79					12	21	38	82	158	258		
34	～		36	110	0	79					15	24	42	99	185	295		35
34	～		36	120	0	79				3	17	28	47	115	215	335	71	
34	～		36	130	0	79				5	19	32	53	128	242	372		
34	～		36	140	0	79				7	21	35	63	156	287	427		
34	～		36	150	0	79				8	23	38	73	179	326	476	165	
34	～		36	160	0	79				11	26	40	81	201	364	524		
34	～		36	170	0	79				14	29	44	88	220	400	570		
36	～		38	10	0	79									5	15		
36	～		38	20	0	79								7	12	32		
36	～		38	30	0	79							6	13	24	54	-2	-3
36	～		38	40	0	79						4	9	21	39	79		-5
36	～		38	50	0	79						7	16	29	57	107		3
36	～		38	60	0	79					3	10	20	40	78	138	4	
36	～		38	70	0	79					5	15	24	48	97	167		
36	～		38	80	0	79					9	16	31	61	122	202		
36	～		38	90	0	79				1	13	20	36	78	153	243	26	
36	～		38	100	0	79				2	15	23	41	94	180	280		
36	～		38	110	0	79				6	16	27	47	112	213	323		

安全率 21～3m:1.00 加圧速度 8m／min 減圧速度 8m／min 水蒸気圧を考慮する → 大気圧:9.433m

帯底圧力 (msw)				高圧下 時間(min)	He(%)	N2(%)	空気呼吸 減圧速度8m/min				空気呼吸 減圧速度8m/min				減圧時間	総業務 時間	別表1 差	別表2 差
を超え			以下				24	21	18	15	12	9	6	3				
36	～		38	120	0	79				8	20	31	53	126	243	363	88	
36	～		38	130	0	79				10	22	35	62	154	288	418		
36	～		38	140	0	79				13	23	38	73	180	332	472		
36	～		38	150	0	79				16	27	40	81	203	372	522	201	
36	～		38	160	0	79			1	18	30	45	90	222	411	571		
38	～		40	10	0	79									5	15		
38	～		40	20	0	79							1	7	13	33		5
38	～		40	30	0	79						1	7	15	28	58	-2	
38	～		40	40	0	79						6	10	24	45	85		
38	～		40	50	0	79					2	8	16	34	65	115		
38	～		40	60	0	79					5	13	21	43	87	147	5	
38	～		40	70	0	79					8	16	26	54	109	179		
38	～		40	80	0	79				2	12	19	34	70	142	222		14
38	～		40	90	0	79				4	15	22	39	86	171	261	31	
38	～		40	100	0	79				8	16	25	45	107	206	306		45
38	～		40	110	0	79				11	19	30	52	122	239	349		
38	～		40	120	0	79				13	22	34	61	148	283	403	122	
38	～		40	130	0	79			2	15	23	38	72	177	332	462		
38	～		40	140	0	79			3	18	27	40	82	202	377	517		
38	～		40	150	0	79			5	19	31	45	91	223	419	569		

※ 他減圧表との差については、プラスが増加、マイナスが減少
※ 最大高圧下の時間は、総作業業務時間が600分を超えない範囲で設定(480分+残業120分)